Neda Libre Services Integration Platform (Neda-LSIP)
Design and Implementation Notes

Draft Document – Reflects Work in Progress

Document Nu: PLPC-110501

Mohsen Banan
http://mohsen.banan.1.byname.net/ContactMe

Version 1.7
January 5, 2008

Contents

I Concept and Model 1

1 Open Services Management Tools 3

1.1 Server To Services Transformation . . . 3
1.2 Open Services Management Tools . . . 3
1.3 GOALS . . . 3
1.4 Common Features . . . 5
1.5 Obtaining LSIP . . . 6
1.6 LSIP License . . . 6
1.7 LSIP Overview . . . 6

II Libraries and Seeds 7

1.8 Libre Platform Definitions . . . 9

III Libre Platform Base 11

2 Open Platform Libraries 13

2.1 doLib . . . 13
2.2 visLib . . . 13
2.3 ocp-lib . . . 14
2.4 ocp-general . . . 14
2.5 ocp-lineNu . . . 16
2.6 ocpLibUse . . . 16
2.7 opRunEnvLib . . . 16
2.8 opWrappersLib . . . 16
2.9 itemsLib . . . 17
2.9.1 Visibility Rules . . . 17
2.9.1.1 items Visibility . . . 17

2.9.1.2 runMode Visibility . . . 18
2.9.1.3 Cluster Visibility . . . 18
2.9.1.4 Binary Visibility . . . 18
2.10 opDoAtAsLib . . . 18

3 Seed Scripts **19**
3.1 seedActions.sh . . . 19
3.1.1 Description . . . 19
3.1.2 Example . . . 23
3.2 seedSubjectAction.sh . . . 23
3.2.1 Description . . . 23
3.2.2 Example . . . 28

IV Base Platform and Site Abstraction **29**

4 Site and Clusters Selection **31**
4.1 opHosts . . . 32
4.2 opSites . . . 32
4.3 opClusters . . . 32
4.4 opDomains . . . 32
4.4.1 opSysIdentities . . . 32

5 Conventions **33**
5.1 Introduction . . . 33
5.1.1 Model and Terminology – MMA Tools . . . 33
5.1.2 Files Overview – MMA Tools . . . 35
5.1.3 Hints – MMA Tools . . . 35
5.1.4 Pointer and References – MMA Tools . . . 35

V Package and Distribution Facilities **37**

6 Linux Distribution Abstractions **39**

7 BinsPrep **41**

8 Operating System Installation **43**
8.1 opGenesis . . . 43

VI Host and Site Administration 45

9 Disk Management Tools 47

9.1 Model and Terminology – Disk Management Tools . . . 48
9.2 Files Overview – Disk Management Tools . . . 52
9.3 Hints – Disk Management Tools . . . 52
9.4 Pointer and References – Disk Management Tools . . . 52

VII Disk and Storage Facilities 53

VIII System Foundation Facilities 55

9.5 MMA Daemon Tools . . . 57
9.5.1 Model and Terminology – MMA Daemon Tools . . . 57
9.5.2 Files Overview – MMA Daemon Tools . . . 57
9.5.3 Hints – MMA Daemon Tools . . . 57
9.5.4 Pointer and References – MMA Daemon Tools . . . 57

IX Network Foundation Facilities 59

10 L2 Facilities 61

11 L3 Facilities 63

11.1 MMA Layer 3 . . . 63
11.1.1 Model and Terminology – MMA Layer 3 . . . 63
11.1.2 Files Overview – MMA Layer 3 . . . 64
11.1.3 Hints – MMA Layer 3 . . . 64
11.1.4 Pointer and References – MMA Layer 3 . . . 65

12 UCSPI 67

12.1 MMA Ucspi . . . 67
12.1.1 Model and Terminology – MMA Ucspi . . . 67
12.1.2 Files Overview – MMA Ucspi . . . 67
12.1.3 Hints – MMA Ucspi . . . 67
12.1.4 Pointer and References – MMA Ucspi . . . 67

13 Misc 69

13.1 MMA FTP . . . 69

13.1.1 Model and Terminology – MMA FTP . . . 69
13.1.2 Files Overview – MMA FTP . . . 69
13.1.3 Hints – MMA FTP . . . 70
13.1.4 Pointer and References – MMA FTP . . . 70
13.2 MMA GNATS . . . 70
13.2.1 Model and Terminology – MMA GNATS . . . 70
13.2.2 Files Overview – MMA GNATS . . . 71
13.2.3 Hints – MMA GNATS . . . 72
13.2.4 Pointer and References – MMA GNATS . . . 72
13.3 MMA Rsync . . . 73
13.3.1 Model and Terminology – MMA Rsync . . . 73
13.3.2 Files Overview – MMA Rsync . . . 73
13.3.3 Hints – MMA Rsync . . . 73
13.3.4 Pointer and References – MMA Rsync . . . 74
13.4 MMA Ssh . . . 74
13.4.1 Model and Terminology – MMA Ssh . . . 74
13.4.2 Files Overview – MMA Ssh . . . 74
13.4.3 Hints – MMA Ssh . . . 75
13.4.4 Pointer and References – MMA Ssh . . . 76
13.5 MMA Sudo . . . 76
13.5.1 Model and Terminology – MMA Sudo . . . 76
13.5.2 Files Overview – MMA Sudo . . . 76
13.5.3 Hints – MMA Sudo . . . 77
13.5.4 Pointer and References – MMA Sudo . . . 77
13.6 MMA Tftp . . . 77
13.6.1 Model and Terminology – MMA Tftp . . . 77
13.6.2 Files Overview – MMA Tftp . . . 77
13.6.3 Hints – MMA Tftp . . . 78
13.6.4 Pointer and References – MMA Tftp . . . 78

X DNS Facilities 79

13.7 MMA DNS . . . 81
13.7.1 Model and Terminology – MMA DNS . . . 81
13.7.2 Files Overview – MMA DNS . . . 83
13.7.3 Hints – MMA DNS . . . 84
13.7.4 Pointer and References – MMA DNS . . . 85

XI Mail Facilities 87

14 Email Facilities 89

14.1 Introduction . . . 89
14.1.1 General Policies & Procedures . . . 89
14.1.2 Site Deployment Policies & Procedures . . . 89
14.2 mmaQmail . . . 91
14.3 Model and Terminology – MMA Qmail Tools . . . 91
14.4 Files Overview – MMA Qmail Tools . . . 93
14.5 Hints – Account Management Tools . . . 95
14.6 Pointer and References – Account Management Tools . . . 96
14.7 MMA Qmail . . . 96
14.7.1 Model and Terminology – MMA Qmail . . . 96
14.7.2 Files Overview – MMA Qmail . . . 98
14.7.3 Hints – MMA Qmail . . . 100
14.7.4 Pointer and References – MMA Qmail . . . 101
14.8 MMA IMAP . . . 101
14.8.1 Model and Terminology – MMA IMAP . . . 101
14.8.2 Files Overview – MMA IMAP . . . 102
14.8.3 Hints – MMA IMAP . . . 103
14.8.4 Pointer and References – MMA IMAP . . . 103

XII Web Facilities 105

15 Web Server Tools 107

15.1 opWebServers . . . 107
15.2 MMA Web . . . 107
15.2.1 Model and Terminology – MMA Web . . . 107
15.2.2 Files Overview – MMA Web . . . 108
15.2.3 Hints – MMA Web . . . 109
15.2.4 Pointer and References – MMA Web . . . 109

XIII Database and Directory Facilities 111

16 Name Services 113

16.1 nedaIPaddr.sh . . . 113
16.2 opNetNameServices . . . 113

17 Directory Services Tools **115**
17.1 Model and Terminology – Directory Services Tools . . . 115
17.2 Files Overview – Directory Services Tools . . . 115
17.3 Hints – Directory Services Tools . . . 115
17.4 Pointer and References – Directory Services Tools . . . 115

18 Data Base Facilities **117**

XIV Security Facilties **119**

19 Key Management – Remote Access **121**

20 Security Tools **123**
20.1 opSecurity . . . 123

XV Development and Analysis Tools **125**

21 Development Facilities **127**
21.1 CVS . . . 127

22 Software Management Tools **129**
22.1 opSwPkgs . . . 129

23 Performance and Monitoring Tools **131**

XVI Libre Content Production and Publication **133**

24 LaTeX **135**

25 Libre Content Processing **137**
25.1 MMA Published Content . . . 137
25.1.1 Model and Terminology – MMA Published Content . . . 137
25.1.2 Files Overview – MMA Published Content . . . 139
25.1.3 Hints – MMA Published Content . . . 139
25.1.4 Pointer and References – MMA Published Content . . . 140
25.2 lcnLcnt . . . 140

26 Image Processing **141**

27 Video Processing **143**

28 Account Management Tools **145**

28.1 Model and Terminology – Account Management Tools 145

28.2 Files Overview – Account Management Tools 145

28.3 Hints – Account Management Tools 145

28.4 Pointer and References – Account Management Tools 146

29 Cron and At Tools **147**

29.1 Model and Terminology – Cron and At Tools 147

29.2 Files Overview – Cron and At Tools 147

29.3 Hints – Cron and At Tools 148

29.4 Pointer and References – Cron and At Tools 149

30 sudo **151**

XVII Common Components – Service and User Environment **153**

XVIII Service Libre Components **155**

31 Printers Management Tools **157**

31.1 opPrHosts 157

31.2 nedaPrint 157

32 Voice Over IP (VoIP) **159**

33 Assigned Names and Numbers **161**

33.1 Password File Accounts 161

33.1.1 Employee Account 161

33.1.2 Contractor Account 161

33.1.3 Alumni Account 161

33.1.4 Associate Account 161

33.1.5 System Program Accounts 161

33.1.6 System Program Groups 162

33.1.7 Subscribers (Authenticated) 162

33.1.8 QMail Virtual Domain 162

34 System Management and Configuration **163**

34.1 Introduction . . . 163
34.2 opSysMgmtActions . . . 164
34.3 nedaSysMgmtActions . . . 164
34.4 dotIntra Cluster . . . 164

XIX User Environment Components 165

35 ByStar Libre Emacs Office Environment (BLEOE) 167

36 Wlan Facilities 169

37 Browser Facilities 171

XX Native Libre Components 173

38 VoRDE 175
38.1 MMA VoRDE . . . 175
38.1.1 Model and Terminology – MMA VoRDE . . . 175
38.1.2 Files Overview – MMA VoRDE . . . 175
38.1.3 Hints – MMA VoRDE . . . 175
38.1.4 Pointer and References – MMA VoRDE . . . 176

39 LEAP 177
39.1 MMA EMSD . . . 177
39.1.1 Model and Terminology – MMA EMSD . . . 177
39.1.2 Files Overview – MMA EMSD . . . 177
39.1.3 Hints – MMA EMSD . . . 177
39.1.4 Pointer and References – MMA EMSD . . . 178

XXI Obsoleted or Deprecated Components 179
39.2 MMA Jetspeed . . . 181
39.2.1 Model and Terminology – MMA Jetspeed . . . 181
39.2.2 Files Overview – MMA Jetspeed . . . 181
39.2.3 Hints – MMA Jetspeed . . . 182
39.2.4 Pointer and References – MMA Jetspeed . . . 184

List of Figures

1.1 Overview of OSMT 4

14.1 MailMeAnywhere Site Deployment 90

List of Tables

Part I

Concept and Model

Chapter 1

Open Services Management Tools

1.1 Server To Services Transformation

GNU/Linux demonstrated that large a complete Operating System can be put together purely in the Free Software model.

Various forms of dedicated servers have been integrated based on GNU/Linux. Such server constructs are ad-hoc integrations demanding much expertise.

Collective collaboration towards transformation of ad-hoc servers based on Free Software into mass usable agents for delivery of Libre Services is the next challenge.

Construction of a set of Application Services requires an important extension beyond the underlying software layer. Construction of a set of Application Services requires the integration of a set of software components together to provide useful functionality to the user.

This integration layer must conform to correct principles of **structure** and **consistency**. Thus Free Services represent an extension of the Free Software model based on structured and consistent integration.

The versatile "Glue" needed to bring about the needed structure and consistency is a crucial element for realization of Libre Services. Much effort has been devoted to creation of the initial implementation of this Glue. See "Open Systems Management Tools", [**?**] for more details.

1.2 Open Services Management Tools

OSMT (Open Services Management Tools) are a set of tools on top of which various consistent polices can be implemented.

This is a collection tools that collectively lets you consistently manage Unix and Linux systems and some of the tools will also manage Windows system.

1.3 GOALS

Key goals for the design has been:

- Be very Unix centric. Focus on Solaris and Linux



Figure 1.1: Overview of OSMT

- Limit use of the tools to what is minimally and genericly available on plain Unix systems. Namely Korn Shell.
- Be consistent in use of the tools. View this work as a collection. Not bits and pieces here and there.
- Don't view the tools as host management tools, view them as domain management and system management tools.
- Support consistent and simultaneous management of multiple domains. Detection of Sites, Domains and Hosts is an integral part of these tools.
- Tools should be location independent.

1.4 Common Features

```
The following features are available to all scripts based on
seedActions.sh and seedSubjectActions.sh

Tracing:     -T <runLevelNumber>  -- Ex: mmaQmailHosts.sh -T 9 ...
Run Mode:    -n <runMode>         -- Ex: mmaQmailHosts.sh -n runSafe ...
Verbose:     -v                   -- Ex: mmaQmailHosts.sh -v
Force Mode:  -f                   -- Ex: mmaQmailHosts.sh -f
Check Mode:  -c                   -- Ex: mmaQmailHosts.sh -c fast

Tracing
=======
            DEFAULT: -T 0

            Trace Number Conventions:

    0: No Tracing
    1: Application Basic Info
    2: Application General Info
    3: Application Function Entry and Exit
         4: Application Debugging
    5: Wrappers Library
    6: Seed Script
    7: Seed Supporting Libraries (eg, doLib.sh)
    8: ocp_library
    9: Quick Debug, usually temporary

Run Mode:
=========
           DEFAULT: runOnly

G_runMode=
   showOnly:           at opDo* just show the args always return 0
   runOnly:            at opDo* just execute
   showRun:            at opDo both runOnly and showOnly
   runSafe:            at opDo both show and run, but if protected
                       then just show
```

```
   showProtected:      Run everything and don't show except for
                       show only protected
   showRunProtected:   Run everything and don't show except for
                       run and show rotected

runSafe = unprotected: showRun, protected: show
showProtected = unprotected: run, protected: show
showRunProtected = unprotected: run, protected: showRun

Verbose Mode:
=============

G_verbose=
   verbose         When Set, verbose format (eg, line nu, time tag, ...)
                   of Tracing and RunMode are selected.

Force Mode:
=============

G_forceMode=
   force           When Set, force/overwrite mode of operation
                   is selected.

Check Mode:
===========

G_checkMode={fast,strict,full}
   fast:           1) Skip asserting and consistency checks.
                   2) Do less than default, invoker will
                      compensate
   strict:         Do asserts and consistency checks.
   full:           1) Do more than default
```

1.5 Obtaining LSIP

http://www.neda.com/libre/lpGenesis.sh

1.6 LSIP License

Afero GPL V3.

1.7 LSIP Overview

Take from presentation.

Part II

Libraries and Seeds

1.8 Libre Platform Definitions

Part III

Libre Platform Base

Chapter 2

Open Platform Libraries

2.1 doLib

The doLib.sh is a place for common features for script that used the seedSubjectAction. This common features includes:

vis_ls	list all of the functions (hence, equivalent to items) inside the itemsFile.
do_list	
do_describe	describing each items in the itemsFile if opItem_description function exist within the item.
do_itemActions	if the item has a list of itemActions, then it will perform all of them.
doLibExamplesOutput	list all of the common examples for the seedSubjectAction script which include common examples (showMe, seedHelp, ls, list, describe) and common debugging.

To use this feature, put the following in each of the seedSubjectAction script:

```
function vis_examples {
    typeset doLibExamples=`doLibExamplesOutput ${G_myName}`
 cat  << _EOF_
EXAMPLES:
${doLibExamples}
--- EVERYTHING ELSE
.....
.....
.....
_EOF_
}
```

2.2 visLib

This library function the same as doLib except this lib is for seedActions script.

2.3 ocp-lib

The ocp-lib loads all of the osmt library. Each of these libraries will be covered in the following sections.

2.4 ocp-general

ocp-general is a collection of several functions which can be used by any scripts. This library will most probably grow over time to simplify tasks.

Function name convention:

- MA_: mail addressing parsing
- ATTR_: Attribute value parsing
- FN_: File Name Manipulation
- USER_: passwd file related activities
- PN_: Path name

The functions included in this library are:

MA_domainPart	Mail address parsing. Print out the domain part. Example: MA_domainPart vendors@neda.com will output neda.com.
MA_localPart	Mail address parsing. Print out the local part. Example: MA_localPart vendors@neda.com will output vendors.
ATTR_leftSide	Attribute value parsing. Print out the left side of the equal sign (=). Example: ATTR_leftSide variable1=value1 will output variable1.
ATTR_rightSide	Attribute value parsing. Print out the right side of the equal sign (=). Example: ATTR_rightSide variable1=value1 will output value1.
FN_prefix	Print out only the basename of a file without the extension. Example: FN_prefix /opt/public/osmt/bin/mmaQmailHosts.sh will output mmaQmailHosts.
FN_extension	Print out only the extension of a basename file. Example: FN_extension /opt/public/osmt/bin/mmaQmailHosts.sh will output sh.
FN_dirsPart	Print out only the directory of a specific file location. Example: FN_dirsPart /opt/public/osmt/bin/mmaQmailHosts.sh will output /opt/public/osmt/bin.
FN_nonDirsPart	Print out only the basename of a specific file location. Example: FN_nonDirsPart /opt/public/osmt/bin/mmaQmailHosts.sh will output mmaQmailHosts.sh.
FN_fileDefunctMake	Make a specific file become no longer active in the system by moving the file into another file and chmod to 0000. It requires 2 arguments. First arg is the name of the file that we want to defunct and second arg is the new name and it should not have existed.

FN_dirDefunctMake	Same as the above except it applies to a directory instead of a file.
FN_FileCreateIfNotThere	Create a null file if it does not exist.
FN_dirCreateIfNotThere	Create a directory if it does not exist using the mkdir command.
FN_dirCreatePathIfNotThere	Create a directory path if it does not exist using mkdir -p command.
FN_fileSymlinkSafeMake	Requires 2 arguments: source/origin of a file (should exist)and the target name. If the target exist, skip the symlink process.
FN_fileSymlinkUpdate	Same as *FN_fileSymlinkSafeMake* except if the target exist, it will remove the old symlink and make a new one.
FN_fileSafeCopy	Required 2 arguments: a source name and a target name. If the target exist, it will skip the copy process.
FN_fileCopy	Same as *FN_fileSafeCopy* except if the target exist, it will overwrite the old file. Use with caution.
FN_fileSafeKeep	Move a file and rename it with a dateTag extension.
FN_dirSafeKeep	Move a directory and rename it with a dteTag extension.
FN_lineIsInFile	Required 2 arguments: string to check and the filename. It will return 0 if the string is found in the file specified and 1 otherwise.
FN_lineAddToFile	Required 3 arguments: string to check, string to be added, the filename.
FN_textReplace	Required 3 arguments: regexp of text to replace, replacement text, and the filename. The regexp of text to replace has to be in the format of ^text.*$.
FN_textReplaceOrAdd	If the text to be replaced exist in the file, it will call *FN_textReplace* otherwise the replacement text will be added to the file.
FN_fileInstall	This is to ensure that we use FSF's install command. In SunOS the location is in /opt/sfw/bin/install.
FN_grep	This is to ensure that we use grep command that supports "-F", "-v", and "-q". In SunOS, the location is /usr/xpg4/bin/grep.
FN_egrep	This is to ensure that we use egrep command that support "-v", "-q".
_opDoRunOnly	
_opDoShowOnly	
_opDoShowRun	
_opDo	
_opDoAssert	
opDoProtectedBegin	
opDoProtectedEnd	
opDoProtected	
USER_isInPasswdFile	Return 0 if a user is in the /etc/passwd file.
USER_loginGivenHomeDir	Required 1 argument: the path to home directory. If the home directory is found in /etc/passwd, it will output his/her loginName and return 0 otherwise it will return 1.
USER_nextLoginNameGet	....
PN_fileVerify	List information about file.
FN_fileRmIfThere	Calling *PN_rmIfThere*.
PN_rmIfThere	If -v is specified, it will enable the verbose mode. You can specified more than 1 file to be removed.
IS_inList	Required 2 arguments: a string to be checked and a list of strings. Return 0 if the string is in the list of strings otherwise return 1.

LIST_getLast	Get the last argument/string in a list.
LIST_getFirst	Get the first argument.
LIST_set	
LIST_minus	
LIST_setMinusResult	
doStderrToStdout	Put standard error to standard output.
G_validateOption	Required 2 arguments: target and a list. If the target is in the list, it will set targetIsValid="TRUE".
G_abortIfNotSupportedOs	Abort the running script if the OS is not supported. The currently supported OS are SunOS and Linux.
G_abortIfNotRunningAsRoot	Abort the running script if the current user is not root.
G_returnIfNotRunningAsRoot	Return 1 if the current user is not root.
G_validateRunOS	Required 1 argument: a list of OS. If the current OS is in the given list, it will set isValid="TRUE" otherwise it will set isValid="FALSE" and exit.
DOS_toFrontSlash	Convert DOS filename to UNIX system filename.
DOS_toBackSlash	
RELID_extractInfo	Information about product's release ID
logActivitySeparator	
buildAndRecord	

2.5 ocp-lineNu

This library contains functions for debugging purposes.

tm_trace	Depending on what the trace level is, will print out information for debugging purposes. For more complete information, see section **??**.
log_event	For loging purposes.
eh_problem	Give out PROBLEM message and continue.
eh_fatal	Give out a FATAL message and exit.

2.6 ocpLibUse

2.7 opRunEnvLib

To setup and verifying the environment configuration on the system.

2.8 opWrappersLib

This script includes these functions:

opNetCfg_paramsGet	Required 2 parameters: clusterName and hostName. Given these 2 parameters, the nedaIPaddr.sh is called and the network setting for this particular cluster and hostname are set.
i_nedaNetParamsGet	Used by the opNetCfg_paramsGet to set all of the network setting as global variables. These global variables are: opNetCfg_ipAddr, opNetCfg_domainName, opNetCfg_netmask, opNetCfg_networkAddr, opNetCfg_defaultRoute.

2.9 itemsLib

itemsLib ia a set of facilities that operate on any item files.

opItem_description	Whenever -i describe is executed, it will call *opItem_description* and this function will look for *iv_descriptionFunction* in each of the item in the itemsFile. If it exist, the description will be printed out.
opItem_selectClusterFiles	
opItem_ifAvailableInvoke	
opItem_isAvailable	It will check whether the item is available to hostMode (by calling *opItem_isAvailableToHostMode*) and if it is within the cluster (by calling *opItem_isWithinClusterScope*). It will return 0 if everything is correct.
opItem_isAvailableToHostMode	
opItem_isAvailableToOs	

opItem_isWithinClusterScope	Subject variables should be all set (iv_itemScopeVisibleHosts, iv_itemScopeVisibleClusters, iv_itemScopeHiddenHosts). Returns:
	`0 if disk within scope and should be acted upon`
	`1 if disk is tagged to be hidden`
	`2 if disk not in the cluster and also not tagged as visible`

2.9.1 Visibility Rules

2.9.1.1 items Visibility

By adding

```
iv_itemScopeVisibleHosts  -- List of hosts outside of the clusters
                             item is visible to
iv_itemScopeVisibleClusters   -- List of clusters, item is visible to
iv_itemScopeHiddenHosts -- List of hosts inside of the clusters
                           item is visible to
```

you can then use *opItem_isWithinClusterScope* to check the visibility of the item.

By adding

```
iv_itemAvailableToHostModes
```

you can then use *opItem_isAvailableToHostMode*.

By adding

```
iv_itemAvailableToOsType  -- matched against opRunOsType
iv_itemAvailableToMachineArch  --  matched against opRunMachineArch
```

you can then use *opItem_isAvailableToOs*.

2.9.1.2 runMode Visibility

2.9.1.3 Cluster Visibility

2.9.1.4 Binary Visibility

2.10 opDoAtAsLib

Chapter 3

Seed Scripts

3.1 seedActions.sh

3.1.1 Description

```
NAME
     seedAction.sh

DESCRIPTION
     seedActions.sh is the basis of a tool for grouping
     a number of functions within a shell script and allowing
     for their execution and maintenance in a consistent way.

     A large number of common features are provided by simply
     loading seedActions.sh.  seedActions.sh integrates itself
     with your script in three stages.

     Below is the diagram of how this seedActions.sh works:

     seedActionsExample.sh       |       seedActions.sh
                                 |
          1 |                    |
            |                    |
            +--------------------+--------------+ Configuration set:
                                                 | - opConfig.sh
                                 |               | Library load:
                                 |            A  | - ocp.lib
                                 |               | GETOPT
            +--------------------+--------------+
          2 |                    |
 Default +  |                    |
 Mandatory  |                    |
 Parameters |                    |
            +--------------------+--------------+
                                 |               | Set the user
```




```
In this description, the routine is:
   part 1 called --> part A executed -->
   part 2 called --> part B executed -->
   part 3 called --> part C executed.

First, mmaExampleActions.sh is calling part 1:

   if [ "${loadFiles}X" == "X" ] ; then
       seedActions.sh -l $0 $@
       exit $?
   fi

As a result, the seedActions.sh is executed and
the first thing that seedActions.sh do is execute Part A:
   - load opConfig.sh
   - load ocp-lib.sh (OCP Library)
   - process GETOPT (get options)

After Part A is executed, mmaExampleActions.sh declare the
default parameter with tags (typeset -t) if any.
This is also known as PRE loading.

     typeset -t FirstName=MANDATORY
     typeset -t LastName=MANDATORY
     typeset -t SubsSelector=""
     .....

This is where all of the necessary parameters are set,
including the default and mandatory parameters.

parameter=value from the command line must match a
typeset -t.
The initial value of mandatory variables is MANDATORY

After all the parameters are set, seedActions.sh
executes Part B:
   - set all of the user's define parameters.
```

```
     After we have all the parameters, part 3 is called
     (POST Loading).  Part 3 only executed if function
     called G_postParamHook exist within the script.

     command line "someFunction" maps to function: vis_someFunction

OPTIONS
     All scripts base on seedActions.sh get getopts with the
     following options:

     -T traceLevel      Use for debuging purposes -- tracing,
                        with traceLevel being a number
                        between 0-9.

     -i         Run a specific visible function within the
                script.

     -p         Specify the required/default parameters.
                parameter=value from the command line must match a
                typeset -t.  For example:
                   -p FirstName=Homer ...

     -l         Specify the file for loading.

     -u         Gives USAGE Info.  The usage info automatically
                lists all visible functions without the prefix "vis_".

VISIBLE FUNCTIONS
     - The visible functions (indicated by prefix vis_) are internal
       functions which are exposed externally.

     - It can accept ARGS on command line.

CONVENTIONS
     - In every script, vis_help is always put on top.
       The idea being that a description of the script
       can always be accessed through "-i help" in the
       command line.

     - Those based on seedActions.sh  should end in a category
       of actions as a VERB. The most generic form is the verb
       Action itself. For example:  mmaSendmailAction.sh

     - The noArgsHook function will be available in some
       of the script.
       If a default action is applicable to a script,
       the noArgsHook is called, if it exists,
       based on the recognition that a default action will be
       performed.
       If noArgsHook is not specified and the script is run with
       no options, then this warning will be displayed:
```

```
       "No action taken.  Specify options.  See -u"

EXAMPLE
     Mandatory parameters:
        the initial value of mandatory variables is MANDATORY
        e.g.
        typeset -t FirstName=MANDATORY

        In order to force this parameter to be set (hence MANDATORY)
        call the opParamMandatoryVerify within the function
        that needs this parameter.  When opParamMandatoryVerify is
        executed, it will check all of the parameters that has initial
        value MANDATORY.  If it is not set, return error.

     Optional parameters:
        the optional parameters has initial value other that MANDATORY.

     vis_help: the vis_help can always be accessed through "-i help"
               in the command line
     Example of usage: anyScript.sh -i help
     Example of code:

        vis_help () {
           cat  << _EOF_
             Put any text here for information related to this script.
           _EOF_

           exit 1
        }

     noArgsHook:
        e.g.

           noArgsHook="noArgsHook"
           noArgsHook() {
             # If no args, default action or usage

             if [ "$*X" == "X" ]
             then
               echo "No Defaults Specified"
               echo "Specify  Options -- See -u for list of visible actions"
               usage
             fi
           }
```

3.1.2 Example

Take a look at mmaExamplesActions.sh

3.2 seedSubjectAction.sh

3.2.1 Description

```
NAME
     seedSubjectAction.sh

DESCRIPTION
     seedSubjectAction.sh is the basis of a tool for grouping
     a number of functions within a shell script and allowing
     for their execution and maintenance in a consistent way.

     A large number of common features are provided by simply
     loading seedSubjectAction.sh.  seedSubjectAction.sh integrates itself
     with your script in three stages.

     Below is the diagram of how this seedSubjectAction.sh works:
```





In this description, the routine is:
part 1 called --> part A executed -->
part 2 called --> part B executed -->
part 3 called --> part C executed.

First, seedSubjectActionExample.sh is calling part 1:

```
if [ "${loadFiles}X" == "X" ] ; then
    seedSubjectAction.sh -l $0 $*
    exit $?
fi
```

As a result, the seedSubjectAction.sh is executed and
the first thing that seedSubjectAction.sh do is execute Part A:
- load opConfig.sh
- load ocp-lib.sh (OCP Library)
- process GETOPT (get options)

After Part A is executed, seedSubjectActionExample.sh declare the
default parameter with tags (typeset -t) if any.
This is also known as PRE loading.

```
if [ "${loadSegment}_" == "PRE_" ] ; then
  # Mandatory parameters
  typeset -t VirDomRoot=MANDATORY
  typeset -t VirDomTLD=MANDATORY

  # Optional parameter = default value
  typeset -t SiteName=xyzPlus
  .....
```

This is where all of the necessary parameters are set,
including the optional and mandatory parameters.

parameter=value from the command line must match a
typeset -t.
The initial value of mandatory variables is MANDATORY
and the optional parameters become the default value.

After all the parameters are set, seedSubjectAction.sh
executes Part B:
- set all of the user's define parameters.

```
     After we have all the parameters, part 3 is called
     (POST Loading). Part 3 only executed if function
     called G_postParamHook exist within the script.

     The setBasicItemsFile is called here. See CONVENTIONS
     section for how setBasicItemsFiles works.
     The itemsFile are loaded from the procSubjectItems file:
         procSubjectItems.<specificCluster>
     where procSubjetItems is the corresponding procSubjects.sh,
     <specificSite> is one of main, office, public, etc.

     When procSubjectItems is executed, itemPre and itemPost
     are defined, if there is any.

     itemPre is a place where all the default and mandatory
     parameters are specified.

     itemPost derived defaults.

     After the itemsFile is loaded, "subject" and "action"
     are defined.

     command line "subject" maps to function:  item_subject
     command line "action"  maps to function:  do_action
     By convention, it calls itemAction_action.


OPTIONS
     All scripts base on seedSubjectAction.sh get getopts with the
     following options:

     -T traceLevel      Use for debuging purposes -- tracing,
                        with traceLevel being a number
                        between 0-9.

     -a         Run the specific action.  The "action"
                automatically lists all the action available
                without the "do_" prefix.
                Also applies to itemCmd_ as well.

     -s         Apply the -a "action" to a specific "subject".
                The "subject" automatically lists all the subject
                available without the "item_" prefix.

     -i         Run a specific visible function within the
                script.

     -p         Specify the required/default parameters.
                parameter=value from the command line must match a
                typeset -t.  For example:
```

```
                -p FirstName=Homer ...

    -l          Specify the file for loading.

    -u          Gives USAGE Info.  The usage info automatically
                lists all visible functions without the prefix "vis_".

CONVENTIONS
    - In every script, vis_help is always put on top.
      The idea being that a description of the script
      can always be accessed through "-i help" in the
      command line.

    - Those based on seedSubjectAction.sh should end
      in the plural of the OBJECT, if there are categories
      of actions related to the objects those as verbs come
      before the plural of the object.
      For example: opDiskDrives.sh or mmaQmailHosts.sh

      The seed of the items file is the singular of the fileName
      plus Items. For example opDiskDriveItems.sh or mmaQmailHostItems.sh.

    - The noArgsHook function will be available in some
      of the script.
      If a default action is applicable to a script,
      the noArgsHook is called, if it exists,
      based on the recognition that a default action will be
      performed.
      If noArgsHook is not specified and the script is run with
      no options, then this warning will be displayed:
      "No action taken.  Specify options.  See -u"

    - The noSubjectHook function will be available in some
      of the script.
      This function will be executed if there is no subject
      specified.

    - The firstSubjectHook and lastSubjectHook are typically
      used when the subject is all.  Most of the time, it will
      be used for printing summary of the itemsFile.

    - setBasicItemsFiles procSubjectItems
      Here are the flow how setBasicItemsFiles works:
       if there is procSubjectItems.main, then add it.
       if there is procSubjectItems.clusterName, then add it.

       if there is none of the above then
       if there is procSubjectItems.site, then add it.

       if there is procSubjectItems.otherName, just ignore it.
```

```
        Here is a scenario:
        - For example, suppose we have all of these files:
          procSubjectItems.main, procSubjectItems.office,
          procSubjectItems.home, procSubjectItems.otherCluster
          and we are running from an office machine environment
          then only procSubjectItems.main and procSubjectItems.office
          are loaded and the other are ignored.

     - The itemsFile policy:
        item_SSSS  (SSSS is the subject)
        itemPre
        iv_specialize
        itemPost
        itemCmd_

     - Built in function:
        list -- built in action
        all  -- built in subject
       Example of use in command line:
        anyScript.sh -s all -a list
       This command will enumerate all the subject item_ entries from
       the ItemsFile and list all of the paramaters corresponding to
       each subject item_.

EXAMPLE
     Mandatory parameters:
     ---------------------
        the initial value of mandatory variables is MANDATORY
        e.g.
        typeset -t FirstName=MANDATORY

     Optional parameters:
     --------------------
        typeset -t FirstName=homer

     vis_help:
     ---------
     the vis_help can always be accessed through "-i help"
     in the command line
     Example of usage: anyScript.sh -i help
     Example of code:

        vis_help () {
           cat  << _EOF_
             Put any thext here for information related to this script.
           _EOF_

           exit 1
        }

     noArgsHook:
```

```
-----------
   e.g.

      noArgsHook="noArgsHook"
      noArgsHook() {
        # If no args, default action or usage

        if [ "$*X" == "X" ]
        then
          echo "No Defaults Specified"
          echo "Specify  Options -- See -u for list of visible actions"
          usage
        fi
      }

Use of parameters in vis_ function:
-----------------------------------
print ${FirstName} will give result "homer".

ItemsFile Selection:
--------------------
There are 2 ways to load the procSubjectItems:
   1. Automatic ItemsFile Selection

           setBasicItemsFiles procSubjectItems

   2. Manual ItemsFile Selection

           ItemsFile=${opSiteControlBase}/${opSiteName}/procSubjectItems.main

do_ description:
----------------
The do_AAA function is the AAA "action" taken to some
"subject" item_.
By convention it calls itemAction_AAA.

itemCmd_ description:
---------------------
```

3.2.2 Example

Take a look at mmaExamplesObjects.sh

Part IV

Base Platform and Site Abstraction

Chapter 4

Site and Clusters Selection

HOST MODE	CLUSTER NAME	ACTION
Unnet	Unclustered	Segments local & no mount
	SomeCluster	Illegal
StandAlone	Unclustered	Segments local & no mount
	SomeCluster	if opRunParamStandAlone is - strict: Segments local & no mount - cluster: Segments local & mount
Cluster	Unclustered	Illegal
	SomeCluster	Mount & links

The logic to find out which site and cluster a system belong to are as follows:

1. Find out which SiteName the systemName belong to.
2. Knowing which siteName, search for host.
3. Knowing the hostName, search for clusterName.
4. Knowing the clusterName, search for Domain.

There are several possible cluster names:

1. office
2. island
3. dmz
4. payk
5. subscriber
6. test

```
  7. public
  8. unclustered

And there are several possible opHostMode:
  1. UnNet (U)
  2. Standalone (S) -- no mount
  3. Clustered (C)
  4. SelfContained (SC) -- mount but no symlink
```

4.1 opHosts

4.2 opSites

4.3 opClusters

4.4 opDomains

4.4.1 opSysIdentities

Chapter 5

Conventions

5.1 Introduction

5.1.1 Model and Terminology – MMA Tools

Extracted by mmaRoadmap.sh -i modelAndTerminology

```
   Terminology and Model:
   ======================

Manipulative Verbs:
-------------------

itemShow -- displays the subject  [pkgShow  -- when pkgManipulators]
compShow -- displays (Componenet) what is in the system

verify   -- compares subject and system
update   -- makes system same as subject
delete   -- removes from system


NetListener
-----------

A Net Listner is network responder dispatched
upon a connection request establishment.

Facilities dispatching Net Listners are:

    - inetd
    - ucspi
    - tcpwrapper

A NetListener can also be a daemon.
```

```
NetListener Modes
-----------------

  - enabled     -- active and responding
  - disabled    -- inactive will not respond
  - standby     -- active but should not be first in dns list


--- NETLISTENER ACTIONS ---
mmaRoadmap.sh  -s tehran -a netListenerEnable
mmaRoadmap.sh  -s tehran -a netListenerDisable
mmaRoadmap.sh  -s tehran -a netListenerShow
mmaRoadmap.sh  -s tehran -a netListenerVerify

Network Services Verbs (inetd and daemons)
------------------------------------------
netListenerEnable   -- inetd add line and HUP
                    -- For daemons upon reboot serviceStart
                    -- For daemons serviceStart

netListenerDisable  -- inetd delete line and HUP
                    -- For daemons upon reboot no action
                    -- For daemons serviceStop

netListenerShow     -- inetd delete line and HUP

netListenerVerify   -- inetd delete line and HUP



Daemon Services Verbs
---------------------
serviceStart    -- init.d/xxx start
serviceStop     -- init.d/xxx stop
serviceRestart  -- init.d/xxx restart


Qualifiers to Manipluative Verbs:
---------------------------------

-f G_forceMode:
-v G_verboseMode:
-c G_checkMode

FULL MANIPLUATORS:

fullVerify   -- compares subject and system
fullUpdate   -- makes system same as subject
fullDelete   -- removes from system
```

```
fullStop     -- Stops ALL services for subject
fullStart    -- Starts ALL services for subject


BinsPrepConventions:
--------------------

    - see mmaBinsPrep.sh

Top Level Facilities:
---------------------

opSysIdentities.sh

opSysMgmtActions.sh

mmaSysMgmtActions.sh

bynameSysMgmtActions.sh
```

5.1.2 Files Overview – MMA Tools

Extracted by mmaRoadmap.sh -i help

5.1.3 Hints – MMA Tools

Extracted by mmaRoadmap.sh -i howTos

```
    C: How Do I Setup a mailing list?
```

5.1.4 Pointer and References – MMA Tools

Extracted by mmaRoadmap.sh -i pointersAndReferences

```
Mma man pages.
```

Part V

Package and Distribution Facilities

Chapter 6

Linux Distribution Abstractions

Chapter 7

BinsPrep

Chapter 8

Operating System Installation

8.1 opGenesis

See PLPC-110101.

Part VI

Host and Site Administration

Chapter 9

Disk Management Tools

This tools are used to keep track/manage all kinds of tasks related to disk drives.

The sort of tasks that this tool performed are:

- ItemsFile: **opDiskDriveItems.site**. This items file keep tracks the disk drives hardware – each disk drive is assigned a letter. Most of them are external drive. In some cases, if the internal disk is large (i.e. more than 2GB) then it will be assigned a letter. The information in this file is as follow (as an example):

```
iv_dd_itemName="a"

iv_dd_diskInfoPartitionCapacity="2GB"
iv_dd_diskShareWith="root swap /export/home"

iv_dd_diskInfoDrive="External"
iv_dd_diskInfoAssetLocation="C8-02-03.02"
iv_dd_diskSerialNumber="621G1815"
```

- ItemsFile: **opDiskDriveUseItems.site**. This items file keep track of the usage of each partition of the disk drive. The purpose of this is to mount the partition on another system. The information in this file is as follow (as an example):

```
iv_du_itemName=${0##item_du_}
iv_diskHostMountPoint="/i1"
iv_diskUsageMountPoint="/i1"

iv_diskHost="jamshid"
iv_diskPurpose="data"
iv_itemScopeVisibleHosts=""
iv_itemScopeHiddenHosts=""
iv_itemScopeVisibleClusters="office"

iv_diskSCSItarget=1

iv_diskPartitionNu=2
iv_diskPartitionSize="18GB"
```

```
iv_diskPartitionSylBegin="0"
iv_diskPartitionSylEnd="35368271"
```

If the iv_itemScopeVisibleClusters is “uncluster” then this partition will not be mounted anywhere at all. The iv_itemScopeHiddenHosts will only apply to the system in the same cluster and iv_itemScopeVisibleHosts will only apply to the system in different cluster.

- ItemsFile: **opDiskSegmentItems.site**. This items file is used for symlink purposes. Visibility applies to multiple hostMode.

The hierarchy of the disk management is depicted in this figure:



9.1 Model and Terminology – Disk Management Tools

Extracted by opDisksRoadmap.sh -i modelAndTerminology

```
   Terminology and Model:
   ======================

opDisksRoadmap.sh               -- Documentation

opDiskDrives.sh                 -- Abstraction of a physical
                                   disk drive. Include
                                   - Disk Name (v)
                                   - Type Internal/External
                                   - Size
                                   - Asset reference
                                   - ...
                                   Gets included (doted) by
                                   diskDriveUses.sh
```

```
                                   The types of things that
                                   can be done are:
                                   * summaries

opDiskDriveUses.sh                 -- How a particular disk drive
                                   is being used.
                                   - Which Host is using
                                   - At what mount point
                                   - With what partitions
                                   Subject to visibility rules.
                                   The types of things that
                                   can be done are:
                                   * localMount
                                   * remoteMount
                                   * export
                                   * summaries

opDiskSegments.sh                  -- Abstraction of a segment
                                   of a disk drive used for a
                                   particular purpose.
                                   The types of things that
                                   can be done are:
                                   * symLinks
                                   * backup
                                   * replications/synchronization


opDiskBackupServers.sh             -- backupSchedule, summaries

mmaRsyncDiskSegments.sh            -- Rsync, ...


ITEM FILES
----------

    - opDiskSegmentItems.main

    - opDiskSegmentItems.{diskName}    -- e.g., t1

    - opDiskSegmentPkgItems.{pkgName}  -- e.g., pubBasics

    - opDiskSegmentImportItems.{diskName}  -- e.g., k1

- opDiskSegmentItems.{diskName} includes:

    - visibility information, for the purpose
      deciding to whether or not a certain item
      is visibile given the host/cluster/mode
      information.

      If not visible, the entire item is ignored.
```

```
    - segement self information.

    - import information

    - export parameters, including
      export/back-up frequency.

- opDiskSegmentPkgItems.{pkgName} is a bounch of
  segements which are to be identical on each
  diskSegemenItems.{driveName} file which includes
  them.

- opDiskSegmentImportItems.{diskName} includes
  information for how to import/export segments on a disk
  being exported/imported by a particular host.

  loading of the container may be repeated within
  each item. Each item refers to its own exporter.

  To distinguish whether a segment is meant to be:
    - an importer (meaning it can only RECEIVE from the outsider),
      it determined by iv_dsImport_methodsList and set
      iv_dsImport_exporterMethodsList to nul.
    - an exporter (meaning it can only SEND OUT to the outsider),
      it determined by iv_dsImport_exporterMethodsList and set
      iv_dsImport_methodsList to nul.
    - an exporter AND an importer set both parameter.

rsyncSshPush and rsyncSshPoll
=============================


                    Push
         +---------<<<<<<<<<<-------------+
         |                               |
         v                               |
    +----------+                    +----------+
    | IMPORTER |                    | EXPORTER |
    +----------+                    +----------+
         |                               ^
         |                               |
         +---------->>>>>>----------------+
                    Poll


IMPORT ACTION
-------------
if the iv_dsImport_methodsList is "rsyncSshPoll" then the action
(segmentsImport) can only be run from the importer site.
The importer REQUEST DATA from the exporter (Import From).
```

```
<Kind of Remote to Local Rsync>

EXPORT ACTION
-------------
if the iv_dsImport_exporterMethodsList is "rsyncSshPush" then the action
(segmentsExport) can only be run from the exporter site.
The exporter PUSH DATA to the importer (Export To).
<Kind of Local To Remote Rsync>

if the iv_dsImport_exporterMethodsList is "rsyncSshPoll" then
the importer may request data from the exporter.

DISKS BACKUP/MIRROR
===================
opDiskBackupServers.sh can be used to backup or
mirror any disks.  Most of the works are done through
opDiskSegments.sh.  The difference between backup and
mirror operation is in the destination's directory
structure.

+-------------------------------------------------------------------------+
|        Source       | Operation |   Destination                         |
+-------------------------------------------------------------------------+
| /x1/opt/public/osmt |   mirror  | /a1/opt/public/osmt                   |
+-------------------------------------------------------------------------+
| /x1/opt/public/osmt |   backup  | /backups/030220124157/x1/opt/public/osmt |
+-------------------------------------------------------------------------+

Related files:
--------------
opDiskDriveUseItems.site         -- opDiskSegments.sh use these items file
            for its subject (i.e -s du_x1)
    In each of the item, there is
    iv_du_segmentsFileRef and it will
    refer to opDiskSegmentItems.xx
opDiskSegmentItems.xx            -- xx is the disk label (e.g. x1,i1, etc)
    Contain information for import/export
    disk segments as well as backup frequency.
opDiskSegmentPkgdItems.pubBasics -- Contain disk segments that are common
    for all disk.
opDiskSegmentImportItems.xx      -- xx is the disk label (e.g. x1,i1, etc)
    Contain disk segment that can be used for
    import/export.  This file is used by
    importer.  So if the segments is in this
    file, the importer can then import this
    segment.
opDiskBackupServerItems.office   -- Contain backup server info.

opDiskBackupServers.sh actions
------------------------------
exportBackup: exporting a segment to remote backup server.
```

```
importBackup: importing a segment to be backuped from a remote host.

Whether a segment need to be backuped or not
is determined by the backup frequency.
If backupFreq is "NONE" then the segment is not subject to
backup.
```

9.2 Files Overview – Disk Management Tools

Extracted by opDisksRoadmap.sh -i help

9.3 Hints – Disk Management Tools

Extracted by opDisksRoadmap.sh -i howTos

```
    Q: How Do I Setup a new disk and prepare it for
       backup?
    A: 1. Add new items file to opDiskDriveUseItems.site
          For example: item_du_x1 where x1 is the
  new disk label.
       2. Create new file named opDiskSegmentItems.x1
          If x1 will have all of the disk segment listed in
  the pkgdItem.pubBasics, do loadPkgd_pubBasics.
  If x1 will have custom segments, add it to this file.
  See example of this custom segments in
  opDiskSegmentItems.v1.  Set the backup frequency.
       3. If x1 will be used by other disk to import
          disk segment from it, create opDiskSegmentImportItems.x1
  file.
```

9.4 Pointer and References – Disk Management Tools

Extracted by opDisksRoadmap.sh -i pointersAndReferences

```
Mma man pages.
```

Part VII

Disk and Storage Facilities

Part VIII

System Foundation Facilities

9.5 MMA Daemon Tools

9.5.1 Model and Terminology – MMA Daemon Tools

Extracted by mmaDaemontoolsRoadmap.sh -i modelAndTerminology

```
- svscan start/stop through /etc/init.d/

Per Service Actions
===================

mmaDaemon{Update,Delete,List,Start,Stop,...}
available through the library.
```

9.5.2 Files Overview – MMA Daemon Tools

Extracted by mmaDaemontoolsRoadmap.sh -i help

9.5.3 Hints – MMA Daemon Tools

Extracted by mmaDaemontoolsRoadmap.sh -i howTos

9.5.4 Pointer and References – MMA Daemon Tools

Extracted by mmaDaemontoolsRoadmap.sh -i pointersAndReferences

Part IX

Network Foundation Facilities

Chapter 10

L2 Facilities

Chapter 11

L3 Facilities

11.1 MMA Layer 3

11.1.1 Model and Terminology – MMA Layer 3

Extracted by mmaLayer3Roadmap.sh -i modelAndTerminology

```
   Terminology and Model:
   ======================

 - subnetworks:

 - interfaces:

Objects Overview:
-----------------

item_l3_server_{HostName}: Config Parameters for the router.


mmaLayer3 Object Processors and Containers:
-------------------------------------------

    mmaLayer3Hosts.sh
```

11.1.2 Files Overview – MMA Layer 3

Extracted by mmaLayer3Roadmap.sh -i help

```
DESCRIPTION
     mmaLayer3 (MailMeAnywhere LAYER3) is a set of consistent
     policies built on the LAYER3 as a CAPABILITY and on
     (OSMT) Open Services Management Tools.

     mmaLayer3 Commands, each contain a set of related functions
     which allow you to accomplish specific tasks. Specifically:

     COMMAND                   TYPE             USED BY

     mmaLayer3.sh               action.sh         any

     mmaLayer3Lib.sh            library.sh        root/any

     mmaLayer3BinsPrep.sh       action.sh         root

     mmaLayer3Hosts.sh         subjectAction.sh  root/any

     mmaLayer3Admin.sh          action.sh         root/any

At A Glance
-----------

Basic layer3
-----------

  mmaLayer3.sh              -- This File. General Orientation and Information

  mmaLayer3Lib.sh           -- To be included in all mmaLayer3 scripts.
                               General configuration parameters and
                               general useful functions go here

  mmaLayer3BinsPrep.sh      -- Prepare binary files for layer3/ezmlm
                            -- for relevant pltforms and versions

  mmaLayer3BinsInstall.sh   -- Install mmaLayer3 binaries on opRunHostName

  mmaLayer3Hosts.sh         -- For subject host, configure layer3
```

11.1.3 Hints – MMA Layer 3

Extracted by mmaLayer3Roadmap.sh -i howTos

```
Config Device Driver Modules -- Net Devices
```

```
Ferm  -- Firewal to iptables high level compiler

Band Width Monitor -- NOTYET

IP Forwarding enabled/disabled
    Through /etc/sysctl.conf
add the following
net/ipv4/ip_forward=1

Bring Up/down Interfaces
ifup
ifdown

ferm generates iptables enteries

What does iptables -t net -L do?

setup_fw?

Load kernel modules #3C59X  VoRTEX
```

11.1.4 Pointer and References – MMA Layer 3

Extracted by mmaLayer3Roadmap.sh -i pointersAndReferences

```
Layer3: http://
```

Chapter 12

UCSPI

12.1 MMA Ucspi

12.1.1 Model and Terminology – MMA Ucspi

Extracted by mmaUcspiRoadmap.sh -i modelAndTerminology

svs

12.1.2 Files Overview – MMA Ucspi

Extracted by mmaUcspiRoadmap.sh -i help

12.1.3 Hints – MMA Ucspi

Extracted by mmaUcspiRoadmap.sh -i howTos

12.1.4 Pointer and References – MMA Ucspi

Extracted by mmaUcspiRoadmap.sh -i pointersAndReferences

Chapter 13

Misc

13.1 MMA FTP

13.1.1 Model and Terminology – MMA FTP

Extracted by mmaFtpRoadmap.sh -i modelAndTerminology

```
   Terminology and Model:
```

13.1.2 Files Overview – MMA FTP

Extracted by mmaFtpRoadmap.sh -i help

```
DESCRIPTION

     mmaFtp is a set of consistent facilities
     on top of wu-ftp which enforces MMA policies.


Basic DNS Scripts
-----------------

  mmaFtp.sh              -- This File. General Orientation and Information

  mmaFtpBinsPrep.sh      -- Prepare binary files for djbFtp
                         -- for relevant pltforms and versions
                         -- Install mmaFtp binaries on opRunHostName

  mmaFtpHosts.sh         -- For subject host, configure qmail
```

```
  mmaFtpAdmin.sh         -- Start, stop and addNewAccounts
```

13.1.3 Hints – MMA FTP

Extracted by mmaFtpRoadmap.sh -i howTos

```
    A-1) How Do I install djbdns on my system?
       Follow the steps below.

       2) Install dns Binaries.
          mmaFtpBinsInstall.sh -i djbdnsFullInstall


       3) Specify basic  paramters (domain, ...)
 In ../siteControl/nedaPlus/mmaFtpListItems.main
 add an entry for your host. Then:

         mmaFtpHosts.sh -s tehran -a configure

       4) Verify and Monitor installation

         mmaFtpAdmin.sh -i fullReport
```

13.1.4 Pointer and References – MMA FTP

Extracted by mmaFtpRoadmap.sh -i pointersAndReferences

```
NOTYET, Pinneke, anything worth mentioning here.
```

13.2 MMA GNATS

13.2.1 Model and Terminology – MMA GNATS

Extracted by mmaGnatsRoadmap.sh -i modelAndTerminology

```
   Terminology and Model:
   ======================



Objects Overview:
-----------------
```

```
mmaGnats Object Processors and Containers:
------------------------------------------

mmaGnatsServerHosts.sh
```

13.2.2 Files Overview – MMA GNATS

Extracted by mmaGnatsRoadmap.sh -i help

```
DESCRIPTION
     mmaGnats (MailMeAnywhere QMAIL) is a set of consistent
     policies built on the QMAIL as a CAPABILITY and on
     (OSMT) Open Services Management Tools.

     mmaGnats Commands, each contain a set of related functions
     which allow you to accomplish specific tasks. Specifically:

     COMMAND                   TYPE             USED BY

     mmaGnats.sh               action.sh         any

     mmaGnatsLib.sh            library.sh        root/any

     mmaGnatsBinsPrep.sh       action.sh         root

     mmaGnatsServerHosts.sh         subjectAction.sh  root/any

     mmaGnatsAdmin.sh          action.sh         root/any


At A Glance
-----------

Basic qmail
-----------

  mmaGnats.sh              -- This File. General Orientation and Information

  mmaGnatsLib.sh           -- To be included in all mmaGnats scripts.
                              General configuration parameters and
                              general useful functions go here

  mmaGnatsBinsPrep.sh      -- Prepare binary files for qmail/ezmlm
                           -- for relevant pltforms and versions

  mmaGnatsBinsInstall.sh   -- Install mmaGnats binaries on opRunHostName
```

```
mmaGnatsServerHosts.sh         -- For subject host, configure qmail

mmaGnatsAdmin.sh         -- Start, stop and addNewAccounts

mmaGnatsUserConfig.sh    -- Setup Per user environment parameters.
```

13.2.3 Hints – MMA GNATS

Extracted by mmaGnatsRoadmap.sh -i howTos

```
   A) How Do I setup a null client from scratch?
      Follow (A-1), and then:


      3) Specify basic null client paramters (smarthost, domain, ...)
In ../siteControl/nedaPlus/mmaGnatsListItems.main
add an entry for your host. Then:

        mmaGnatsHosts.sh -s tehran -a configure

      4) Verify and Monitor installation

        mmaGnatsAdmin.sh -i fullReport

      5) Sendout a test message.

mmaGnatsUserConfig.sh -i mailTest

      6) Allow users to customize their desired parameters.

        mmaGnatsUserConfig.sh
```

13.2.4 Pointer and References – MMA GNATS

Extracted by mmaGnatsRoadmap.sh -i pointersAndReferences

```
cgi-bin is: /usr/lib/cgi-bin/gnatsweb.pl

Gnats web conf params are in: /etc/gnatsweb/

Web config is in: + /usr/doc/gnatsweb/CUSTOMIZE.vars.gz
```

13.3 MMA Rsync

13.3.1 Model and Terminology – MMA Rsync

Extracted by mmaRsyncRoadmap.sh -i modelAndTerminology

```
   Terminology and Model:
   ======================

pubCntntSrvr:        The server assigned for publishing
                     a set of mmaRsyncPkgs.
```

13.3.2 Files Overview – MMA Rsync

Extracted by mmaRsyncRoadmap.sh -i help

```
At A Glance
-----------

  mmaRsync.sh              -- This File. General Orientation and Information

  mmaRsyncLib.sh           -- To be included in all mmaRsync scripts.
                              General configuration parameters and
                              general useful functions go here

  mmaRsyncPkgs.sh         -- Prepare binary files for qmail/ezmlm
                             -- for relevant pltforms and versions

  mmaRsyncServers.sh      -- Prepare binary files for qmail/ezmlm
```

13.3.3 Hints – MMA Rsync

Extracted by mmaRsyncRoadmap.sh -i howTos

```
    A) How Do I setup a xxx scratch?
```

13.3.4 Pointer and References – MMA Rsync

Extracted by mmaRsyncRoadmap.sh -i pointersAndReferences

13.4 MMA Ssh

13.4.1 Model and Terminology – MMA Ssh

Extracted by mmaSshRoadmap.sh -i modelAndTerminology

```
   Terminology and Model:
   ======================

    Host Key        -- priv/pub key for this host.
    Known Hosts     -- pub keys of remote hosts

    User Key        -- priv/pub key of a user at this host
    AuthorzedKeys   -- pub key of remote users at remote hosts
                    -- granted access

    User Key Export -- Process of exporting the public
                    -- key of a user to other remote users
```

13.4.2 Files Overview – MMA Ssh

Extracted by mmaSshRoadmap.sh -i help

```
DESCRIPTION

     mmaSsh (MailMeAnywhere Open SSH) is a set of consistent
     policies built on the SSH as a CAPABILITY and on
     (OSMT) Open Services Management Tools.

At A Glance
-----------

Basic SSH
-----------

  mmaSsh.sh              -- This File. General Orientation and Information

  mmaSshBinsPrep.sh      -- Prepare binary files for OpenSSH
                         -- for relevant platforms and versions
                         -- Install mmaSsh binaries on opRunHostName
```

```
  mmaSshAdmin.sh         -- Start, stop


USAGE
     See specific mmaSshXxxx  commands.

EXAMPLES

    A) How Do I install OpenSSH on my system?
       Follow the steps below.

       1) Install OpenSSH Binaries.
          mmaSshBinsPrep.sh sshFullInstall

    B) After the installation, what are the next steps?

       1) First, you need to generate the ssh key server
          in order to start ssh daemon. Run the following:
          mmaSshAdmin.sh -i serverKeyGeneration

          This process may take a while.

       2) Start running the sshd as root
  mmaSshAdmin.sh -i start

       3) Generate a key for yourself.  The default forUser is
          the current user login.
          mmaSshAdmin.sh -i userKeyGeneration
          or
          mmaSshAdmin.sh -p forUser=somename -i userKeyGeneration

       4) Try ssh from another machine to the ssh server
          that you just install.


FILES
      mmaSsh*
      tehran
      Linux
```

13.4.3 Hints – MMA Ssh

Extracted by mmaSshRoadmap.sh -i howTos

13.4.4 Pointer and References – MMA Ssh

Extracted by mmaSshRoadmap.sh -i pointersAndReferences

13.5 MMA Sudo

13.5.1 Model and Terminology – MMA Sudo

Extracted by mmaSudoRoadmap.sh -i modelAndTerminology

```
   Terminology and Model:
   ======================

    sudoers file    -- list of which users may excute what
                    -- This file is /etc/sudoers
                    -- man sudoers for more info
```

13.5.2 Files Overview – MMA Sudo

Extracted by mmaSudoRoadmap.sh -i help

```
DESCRIPTION

     mmaSudo is a set of consistent
     policies built on sudo as a CAPABILITY and on
     (OSMT) Open Services Management Tools.

     sudo is able to execute a command as another user.

At A Glance
-----------

Basic Sudo
-----------

  mmaSudo.sh             -- This File. General Orientation and Information

  mmaSudoBinsPrep.sh     -- Prepare binary files for sudo

  mmaSudoAdmin.sh        -- To update the sudoers file


USAGE
     See specific mmaSshXxxx  commands.

EXAMPLES
```

```
    A) How Do I install sudo on my system?
       Follow the steps below.

       1) Install sudo Binaries.
          mmaSudoBinsPrep.sh -i fullUpdate

    B) After the installation, what are the next steps?

       1) Add the user that will allow to run sudo to
          the sudoers file with mmaSudoAdmin.sh

FILES
      mmaSudo*
      tehran
      Linux
```

13.5.3 Hints – MMA Sudo

Extracted by mmaSudoRoadmap.sh -i howTos

13.5.4 Pointer and References – MMA Sudo

Extracted by mmaSudoRoadmap.sh -i pointersAndReferences

13.6 MMA Tftp

13.6.1 Model and Terminology – MMA Tftp

Extracted by mmaTftpRoadmap.sh -i modelAndTerminology

```
   Terminology and Model:
```

13.6.2 Files Overview – MMA Tftp

Extracted by mmaTftpRoadmap.sh -i help

```
DESCRIPTION

     mmaTftp is a set of consistent facilities
     on top of wu-ftp which enforces MMA policies.


Basic DNS Scripts
-----------------

  mmaTftp.sh              -- This File. General Orientation and Information

  mmaTftpBinsPrep.sh      -- Prepare binary files for djbFtp
                          -- for relevant pltforms and versions
                          -- Install mmaTftp binaries on opRunHostName

  mmaTftpHosts.sh         -- For subject host, configure qmail

  mmaTftpAdmin.sh         -- Start, stop and addNewAccounts
```

13.6.3 Hints – MMA Tftp

Extracted by mmaTftpRoadmap.sh -i howTos

```
    A-1) How Do I install djbdns on my system?
       Follow the steps below.

       2) Install dns Binaries.
          mmaTftpBinsInstall.sh -i djbdnsFullInstall


       3) Specify basic  paramters (domain, ...)
 In ../siteControl/nedaPlus/mmaTftpListItems.main
 add an entry for your host. Then:

         mmaTftpHosts.sh -s tehran -a configure

       4) Verify and Monitor installation

         mmaTftpAdmin.sh -i fullReport
```

13.6.4 Pointer and References – MMA Tftp

Extracted by mmaTftpRoadmap.sh -i pointersAndReferences

```
NOTYET, Pinneke, anything worth mentioning here.
```

Part X

DNS Facilities

13.7 MMA DNS

13.7.1 Model and Terminology – MMA DNS

Extracted by mmaDnsRoadmap.sh -i modelAndTerminology

```
   Terminology and Model:

   Qualifiers:
   -----------
        - local:    The scope is limited to this host only.
                    Accomplished using the 127.x.x.x address space.

        - net:      The scope is limited to this host only.
                    Accomplished using the network address space
    (192.168.x.x, ....)

   Server Types:
   -------------

        - Resolving Server:  Runs some form of dnscache.

        - Orig Content Server: Runs tinydns and is the origin of data
                               and provides its data to CopyContentServers.

        - Copy Content Server: Runs tinydns and gets its data from
                               some Orig Content Server.

        - Zone Xfer Server:  Runs axfrdns and provides zone data.


   Copying - Import/Export
   -----------------------

        We dont use "Primary" or "Secondary" terminology.

        We dont use "Master" or "Slave" terminology.

We use Import and Export combined with
        net{Orig,Copy}ContentServer

A net{Orig,Copy}ContentServer when exposed to the
        outside world can be considered Primary or Secondary.

A localOrigContentServer can be exporting to multiple
        netCopyContentServers.

Import and Export Methods are listed below:
```

```
Import Methods:
---------------

   sshPoll                  --
                            --

   ZoneXferGet:             -- Sets up what it takes to do periodic
                            -- axfr-get.


Export Methods:
---------------

   sshPush                  --
                            --


Content Loading:
----------------

   mmaDnsEntry{type}{verb}  -- Takes domainName and HostName (mma)

   mmaDnsEntry{type}{verb}  -- Takes domainName and IpAddress

   type is one of:    {host,alias,mx,childns,...}

   verb is one of:    {show,update,delete}


Exposed Content Servers
-----------------------

  Combinations of netOrig and netCopy contentServers which
  have been declared to higher zones (e.g. root servers).


dnsSetup (Valid Values):
------------------------

   localResolvingServer     -- local cache -- Just available to this host
                            -- runs dnscache on local 127.x address

   netResolvingServer       -- external cache -- net
                            -- runs dnscachex on network IP address

   localOrigContentServer   -- Orig Content Server -- Local Address
                            -- runs tinydns on local 127.x address

   netOrigContentServer     -- Orig Content Server -- Network Address
                            -- runs tinydns on network 192.168 address
```

```
     localCopyContentServer   -- Copy Content Server -- Local Address
                              -- runs tinydns on local 127.x address

     netCopyContentServer     -- Copy Content Server -- Network Address
                              -- runs tinydns on private 192.168 address

     netZoneXferServer:       -- Runs axfrdns and provides zone data.
                              -- Respond to zone transfer requests.

     netZoneXferGet:          -- Setup axfr-get polls



   Permitted Combinations
   ----------------------
localResolvingServer with
netOrigContentServer
                               netCopyContentServer
                               netZoneXferServer

       netResolvingServer (privateResolvingServer or publicResolvingServer)
                               localOrigContentServer
                               localCopyContentServer
                               netZoneXferServer


   Conflicting Combinations
   ------------------------
netResolvingServer and (netOrigContentServer or netCopyContentServer)
```

13.7.2 Files Overview – MMA DNS

Extracted by mmaDnsRoadmap.sh -i help

```
DESCRIPTION

     mmaDns is a set of consistent facilities
     on top of DJBDNS which enforces MMA policies.


Basic DNS Scripts
-----------------

  mmaDns.sh              -- This File. General Orientation and Information

  mmaDnsLib.sh           -- To be included in all mmaDns scripts.
                              General configuration parameters and
```

```
                            general useful functions go here

  mmaDnsBinsPrep.sh      -- Prepare binary files for djbDns
                         -- for relevant pltforms and versions
                         -- Install mmaDns binaries on opRunHostName

  mmaDnsServerHosts.sh   -- For subject host, configure qmail

  mmaDnsAdmin.sh         -- Start, stop and addNewAccounts

  mmaDnsImports.sh       -- Manipulate import zones

  opDomainContents.sh    -- Fill in the data for orig data servers
                         --

  opDomains.sh           -- List of all domains and pointers to the
                         -- content

  opNetNameServices.sh   -- /etc/hosts file generator and domain content
                         -- basic ip address generation.


Basic DNS Items File
--------------------

Related Items Files:

          nedaIPAddrxxxxxItems.{priv0,pubC}

          opDomainItems.site

Basic Items Files:

           mmaDnsServerHostItems.site

           mmaDnsCopyItems.site

           mmaDnsCopyItems.other

----------
```

13.7.3 Hints – MMA DNS

Extracted by mmaDnsRoadmap.sh -i howTos

```
    A-1) How Do I install djbdns on my system?
       Follow the steps below.
```

```
      2) Install dns Binaries.
         mmaDnsBinsInstall.sh -i djbdnsFullInstall


      3) Specify basic  paramters (domain, ...)
In ../siteControl/nedaPlus/mmaDnsListItems.main
add an entry for your host. Then:

        mmaDnsHosts.sh -s tehran -a configure

      4) Verify and Monitor installation

        mmaDnsAdmin.sh -i fullReport
```

13.7.4 Pointer and References – MMA DNS

Extracted by mmaDnsRoadmap.sh -i pointersAndReferences

```
Web draws a directed graph for a domain.
http://www.foobar.tm/dns/dnsbajaj.cgi


Life With DJBDns: http://
```

Part XI

Mail Facilities

Chapter 14

Email Facilities

14.1 Introduction

14.1.1 General Policies & Procedures

14.1.2 Site Deployment Policies & Procedures

The abbreviations that are used in Figure 14.1

EMR-IN: Edge Mail Router - Inbound
MB provide the description.

EMR-OUT: Edge Mail Router - Outbound
MB provide the description.

SMR-DS: Site Mail Router - Delivery Server
MB provide the description.

SMR-DS-LIST: Site Mail Router - Delivery Server - List
MB provide the description.

SMR-SS: Site Mail Router - Submit Server
MB provide the description.

SMR-SA: Site Mail Router - Submission Agent
MB provide the description.

MBAS: Mail Box Access Server
MB provide the description.

FDS: Final Delivery Server
MB provide the description.

MUA: Mail User Agent
MB provide the description.

MRUA: Mail Retrieval User Agent
MB provide the description.



Figure 14.1: MailMeAnywhere Site Deployment

MSUA: Mail Submission User Agent
MB provide the description.

14.2 mmaQmail

14.3 Model and Terminology – MMA Qmail Tools

Extracted by mmaQmailRoadmap.sh -i modelAndTerminology

```
   Terminology and Model:
   ======================

 - FQMA:          Full Qualified Mail Address -- localPart@domainPart

 - localPart:     Stuff to the left of @ sign

 - domainPart:    Domain to the right of @ sign

 - qmailAddr:     A tupple of (localPart) and qmailCtlFile

 - qmailCtlFile:  A .qmail or .qmail-xxx file

 - qmailAccount:  A system account recorded in the users/include

 - locDeliveryAcct: same as qmailAccount

 - qmailDomainType:  One of virDomain or mainDomain

 - mbox:          A file specification in a qmailCtlFile.
                  Multiple localPart and qmailAddr may
                  share the same mbox

 - progs:         A pipe specification in a qmailCtlFile.

 - forwards:      A pipe specification in a qmailCtlFile.


Objects Overview:
-----------------

item_qmailHost_{HostName}: Config Parameters for the mail server host.

                           Server Type is on of:
                           (submitClientSmtp|submitServerSmtp|fullServer)

                           Objects below apply to fullServer.

item_qmailDom_{domainName}: Information about a domain.
```

```
                          Both mainDomain and virDomain object types.
                          Includes pointers back to item_qmailHost and
                          forward to item_qmailAcctsList.

item_qmailAcctsList_{domainName}:  List of item_qmailAcct for domainName

item_qmailAcct:  Tupple of
                 1) systemAcct
                 2) List of item_qmailAddr

item_qmailAddr:
                 - addrName  (localPart)
                 - type ((alias|virDom)=tldAddr, person, prog)
                 - mbox
                 - forward
                 - ...

item_distList:
                 - name
                 - postingRestrictions
                 - archiving
                 - ...

byname/NSP/mailAddr:
                 - byname mail boxes


mmaQmail Object Processors and Containers:
------------------------------------------

    mmaQmailHosts.sh

    mmaQmailDoms.sh

    mmaQmailAddrs.sh

    mmaQmailLists.sh

    bynameNspMail.sh


qmailHost Objects:
------------------

    qmailHost can be of the types:


     submitClientSmtp: Sometimes called "Null Client:
                       Just submits. Doe not accept smtp
                       connections.
```

```
     submitServerSmtp:

     fullServer:
```

14.4 Files Overview – MMA Qmail Tools

Extracted by mmaQmailRoadmap.sh -i help

```
NAME
     mmaQmailRoadmap.sh

SYNOPSIS
     Derived from seedActions.sh, use the -u.
     mmaQmailRoadmap.sh -u

DESCRIPTION
     mmaQmail (MailMeAnywhere QMAIL) is a set of consistent
     policies built on the QMAIL as a CAPABILITY and on
     (OSMT) Open Services Management Tools.

     mmaQmail Commands, each contain a set of related functions
     which allow you to accomplish specific tasks. Specifically:

     COMMAND                   TYPE             USED BY

     mmaQmail.sh               action.sh         any

     mmaQmailLib.sh            library.sh        root/any

     mmaQmailBinsPrep.sh       action.sh         root

     mmaQmailHosts.sh         subjectAction.sh  root/any

     mmaQmailDoms.sh          subjectAction.sh  root/any

     mmaQmailAddrs.sh         subjectAction.sh  root/any

     mmaQmailAdmin.sh          action.sh         root/any

     mmaQmailInject.sh          action.sh         any

     mmaQmailLists.sh         subjectAction.sh  root/any

     mmaQmailUserConfig.sh     action.sh         any

     bynameNspMail.sh         subjectAction.sh  root/any
```

```
At A Glance
-----------

Basic qmail
-----------

  mmaQmail.sh              -- This File. General Orientation and Information

  mmaQmailLib.sh           -- To be included in all mmaQmail scripts.
                              General configuration parameters and
                              general useful functions go here

  mmaQmailBinsPrep.sh      -- Prepare binary files for qmail/ezmlm
                           -- for relevant pltforms and versions

  mmaQmailBinsInstall.sh   -- Install mmaQmail binaries on opRunHostName

  mmaQmailHosts.sh         -- For subject host, configure qmail

  mmaQmailAdmin.sh         -- Start, stop and addNewAccounts

  mmaQmailUserConfig.sh    -- Setup Per user environment parameters.

  mmaQmailAddrs.sh         -- mmaQmailAddrItems specify addresses (e.g. postmaster)
                           -- to be genarted as .qmail- files.

qmailDom
-----------

  mmaQmailDoms.sh           -- mmaQmailVirDomItems.site specifies visible virtual domains.
                            -- Verify and ensure creation of accounts
                            -- for virtual domains (e.g. esro.org and lists.esro.org)
                            -- add the virtual domains to qmail host configurations.


qmail Mailing Lists
-------------------

  mmaQmailLists.sh          -- mmaQmailListItems specify information needed to create
                            -- and activate needed mailing lists.
                            -- Archiving, web exposure (mhonarc) are all done
                            -- here.

ByName Support
--------------

  bynameNspMail.sh          -- Generate and maintain addresses

  bynameNspMailList.sh      -- Track and control mailing list generation
```

```
USAGE
     See specific mmaQmailXxxx  commands.


EXIT STATUS
         opClusterName   The cluster name

FILES
      mmaQmail*
```

14.5 Hints – Account Management Tools

Extracted by mmaQmailRoadmap.sh -i howTos

```
    A-1) How Do I install Qmail on my system?
       Follow the steps below.

       0) Setup Open Services Platform Environment.
          In /opt/public/osmt/bin/
          source opEnvSet.csh -- . opEnvSet.ksh

       1) Disable the existing sendmail functionality
          mmaSendmailActions.sh -i sendmailDefunct

       2) Install Qmail Binaries.
          mmaQmailBinsInstall.sh -i qmailFullInstall


    A) How Do I setup a null client from scratch?
       Follow (A-1), and then:


       3) Specify basic null client paramters (smarthost, domain, ...)
         In ../siteControl/nedaPlus/mmaQmailListItems.main
         add an entry for your host. Then:

         mmaQmailHosts.sh -s tehran -a configure

       4) Verify and Monitor installation

         mmaQmailAdmin.sh -i fullReport

       5) Sendout a test message.

         mmaQmailUserConfig.sh -i mailTest
```

```
      6) Allow users to customize their desired parameters.

        mmaQmailUserConfig.sh

   B: How do I create a new binary kit for a new rev of Linux/SunOs?

      mmaQmailBinsPrep.sh -i mmaQmailBuildAndInstall
      mmaQmailBinsPrep.sh -i mmaQmailBinKitMake

   C: How Do I Setup an Domain Mail Server?

   C: How Do I Setup a mailing list?
```

14.6 Pointer and References – Account Management Tools

Extracted by mmaQmailRoadmap.sh -i pointersAndReferences

```
Life With Qmail: http://
```

14.7 MMA Qmail

14.7.1 Model and Terminology – MMA Qmail

Extracted by mmaQmailRoadmap.sh -i modelAndTerminology

```
  Terminology and Model:
  ======================

- FQMA:          Full Qualified Mail Address -- localPart@domainPart

- localPart:     Stuff to the left of @ sign

- domainPart:    Domain to the right of @ sign

- qmailAddr:     A tupple of (localPart) and qmailCtlFile

- qmailCtlFile:  A .qmail or .qmail-xxx file

- qmailAccount:  A system account recorded in the users/include

- locDeliveryAcct: same as qmailAccount

- qmailDomainType:  One of virDomain or mainDomain
```

```
 - mbox:          A file specification in a qmailCtlFile.
                  Multiple localPart and qmailAddr may
                  share the same mbox

 - progs:         A pipe specification in a qmailCtlFile.

 - forwards:      A pipe specification in a qmailCtlFile.


Objects Overview:
-----------------

item_qmailHost_{HostName}: Config Parameters for the mail server host.

                           Server Type is on of:
                           (submitClientSmtp|submitServerSmtp|fullServer)

                           Objects below apply to fullServer.

item_qmailDom_{domainName}: Information about a domain.
                            Both mainDomain and virDomain object types.
                            Includes pointers back to item_qmailHost and
                            forward to item_qmailAcctsList.

item_qmailAcctsList_{domainName}:  List of item_qmailAcct for domainName

item_qmailAcct:  Tupple of
                 1) systemAcct
                 2) List of item_qmailAddr

item_qmailAddr:
                 - addrName  (localPart)
                 - type ((alias|virDom)=tldAddr, person, prog)
                 - mbox
                 - forward
                 - ...

item_distList:
                 - name
                 - postingRestrictions
                 - archiving
                 - ...

byname/NSP/mailAddr:
                 - byname mail boxes


mmaQmail Object Processors and Containers:
------------------------------------------
```

```
    mmaQmailHosts.sh

    mmaQmailDoms.sh

    mmaQmailAddrs.sh

    mmaQmailLists.sh

    bynameNspMail.sh


qmailHost Objects:
------------------

    qmailHost can be of the types:


     submitClientSmtp: Sometimes called "Null Client:
                       Just submits. Doe not accept smtp
                       connections.

     submitServerSmtp:

     fullServer:
```

14.7.2 Files Overview – MMA Qmail

Extracted by mmaQmailRoadmap.sh -i help

```
NAME
     mmaQmailRoadmap.sh

SYNOPSIS
     Derived from seedActions.sh, use the -u.
     mmaQmailRoadmap.sh -u

DESCRIPTION
     mmaQmail (MailMeAnywhere QMAIL) is a set of consistent
     policies built on the QMAIL as a CAPABILITY and on
     (OSMT) Open Services Management Tools.

     mmaQmail Commands, each contain a set of related functions
     which allow you to accomplish specific tasks. Specifically:

     COMMAND                   TYPE             USED BY

     mmaQmail.sh               action.sh         any

     mmaQmailLib.sh            library.sh        root/any
```

```
     mmaQmailBinsPrep.sh       action.sh         root

     mmaQmailHosts.sh         subjectAction.sh  root/any

     mmaQmailDoms.sh         subjectAction.sh  root/any

     mmaQmailAddrs.sh         subjectAction.sh  root/any

     mmaQmailAdmin.sh          action.sh         root/any

     mmaQmailInject.sh          action.sh         any

     mmaQmailLists.sh         subjectAction.sh  root/any

     mmaQmailUserConfig.sh     action.sh         any

     bynameNspMail.sh         subjectAction.sh  root/any


At A Glance
-----------

Basic qmail
-----------

  mmaQmail.sh              -- This File. General Orientation and Information

  mmaQmailLib.sh           -- To be included in all mmaQmail scripts.
                              General configuration parameters and
                              general useful functions go here

  mmaQmailBinsPrep.sh      -- Prepare binary files for qmail/ezmlm
                           -- for relevant pltforms and versions

  mmaQmailBinsInstall.sh   -- Install mmaQmail binaries on opRunHostName

  mmaQmailHosts.sh         -- For subject host, configure qmail

  mmaQmailAdmin.sh         -- Start, stop and addNewAccounts

  mmaQmailUserConfig.sh    -- Setup Per user environment parameters.

  mmaQmailAddrs.sh         -- mmaQmailAddrItems specify addresses (e.g. postmaster)
                           -- to be genarted as .qmail- files.

qmailDom
-----------

  mmaQmailDoms.sh           -- mmaQmailVirDomItems.site specifies visible virtual domains.
                            -- Verify and ensure creation of accounts
```

```
                          -- for virtual domains (e.g. esro.org and lists.esro.org)
                          -- add the virtual domains to qmail host configurations.


qmail Mailing Lists
-------------------

  mmaQmailLists.sh        -- mmaQmailListItems specify information needed to create
                          -- and activate needed mailing lists.
                          -- Archiving, web exposure (mhonarc) are all done
                          -- here.

ByName Support
--------------

  bynameNspMail.sh        -- Generate and maintain addresses

  bynameNspMailList.sh    -- Track and control mailing list generation


USAGE
     See specific mmaQmailXxxx  commands.


EXIT STATUS
         opClusterName   The cluster name

FILES
      mmaQmail*
```

14.7.3 Hints – MMA Qmail

Extracted by mmaQmailRoadmap.sh -i howTos

```
    A-1) How Do I install Qmail on my system?
       Follow the steps below.

       0) Setup Open Services Platform Environment.
          In /opt/public/osmt/bin/
          source opEnvSet.csh -- . opEnvSet.ksh

       1) Disable the existing sendmail functionality
          mmaSendmailActions.sh -i sendmailDefunct

       2) Install Qmail Binaries.
          mmaQmailBinsInstall.sh -i qmailFullInstall
```

```
A) How Do I setup a null client from scratch?
   Follow (A-1), and then:


   3) Specify basic null client paramters (smarthost, domain, ...)
     In ../siteControl/nedaPlus/mmaQmailListItems.main
     add an entry for your host. Then:

     mmaQmailHosts.sh -s tehran -a configure

   4) Verify and Monitor installation

     mmaQmailAdmin.sh -i fullReport

   5) Sendout a test message.

     mmaQmailUserConfig.sh -i mailTest

   6) Allow users to customize their desired parameters.

     mmaQmailUserConfig.sh

B: How do I create a new binary kit for a new rev of Linux/SunOs?

   mmaQmailBinsPrep.sh -i mmaQmailBuildAndInstall
   mmaQmailBinsPrep.sh -i mmaQmailBinKitMake

C: How Do I Setup an Domain Mail Server?

C: How Do I Setup a mailing list?
```

14.7.4 Pointer and References – MMA Qmail

Extracted by mmaQmailRoadmap.sh -i pointersAndReferences

```
Life With Qmail: http://
```

14.8 MMA IMAP

14.8.1 Model and Terminology – MMA IMAP

Extracted by mmaImapRoadmap.sh -i modelAndTerminology

```
   Terminology and Model:
   ======================



Objects Overview:
-----------------



mmaGnats Object Processors and Containers:
------------------------------------------

mmaGnatsServerHosts.sh
```

14.8.2 Files Overview – MMA IMAP

Extracted by mmaImapRoadmap.sh -i help

```
DESCRIPTION
     mmaGnats (MailMeAnywhere QMAIL) is a set of consistent
     policies built on the QMAIL as a CAPABILITY and on
     (OSMT) Open Services Management Tools.

     mmaGnats Commands, each contain a set of related functions
     which allow you to accomplish specific tasks. Specifically:

     COMMAND                   TYPE             USED BY

     mmaGnats.sh               action.sh         any

     mmaGnatsLib.sh            library.sh        root/any

     mmaGnatsBinsPrep.sh       action.sh         root

     mmaGnatsServerHosts.sh         subjectAction.sh  root/any

     mmaGnatsAdmin.sh          action.sh         root/any


At A Glance
-----------

Basic qmail
-----------

  mmaGnats.sh              -- This File. General Orientation and Information

  mmaGnatsLib.sh           -- To be included in all mmaGnats scripts.
```

```
                            General configuration parameters and
                            general useful functions go here

  mmaGnatsBinsPrep.sh      -- Prepare binary files for qmail/ezmlm
                           -- for relevant pltforms and versions

  mmaGnatsBinsInstall.sh   -- Install mmaGnats binaries on opRunHostName

  mmaGnatsServerHosts.sh         -- For subject host, configure qmail

  mmaGnatsAdmin.sh         -- Start, stop and addNewAccounts

  mmaGnatsUserConfig.sh    -- Setup Per user environment parameters.
```

14.8.3 Hints – MMA IMAP

Extracted by mmaImapRoadmap.sh -i howTos

```
   A) How Do I setup a null client from scratch?
      Follow (A-1), and then:


      3) Specify basic null client paramters (smarthost, domain, ...)
In ../siteControl/nedaPlus/mmaGnatsListItems.main
add an entry for your host. Then:

        mmaGnatsHosts.sh -s tehran -a configure

      4) Verify and Monitor installation

        mmaGnatsAdmin.sh -i fullReport

      5) Sendout a test message.

mmaGnatsUserConfig.sh -i mailTest

      6) Allow users to customize their desired parameters.

        mmaGnatsUserConfig.sh
```

14.8.4 Pointer and References – MMA IMAP

Extracted by mmaImapRoadmap.sh -i pointersAndReferences

```
cgi-bin is: /usr/lib/cgi-bin/gnatsweb.pl

Gnats web conf params are in: /etc/gnatsweb/

Web config is in: + /usr/doc/gnatsweb/CUSTOMIZE.vars.gz
```

Part XII

Web Facilities

Chapter 15

Web Server Tools

15.1 opWebServers

15.2 MMA Web

15.2.1 Model and Terminology – MMA Web

Extracted by mmaWebRoadmap.sh -i modelAndTerminology

```
   Terminology and Model:
   ======================

Objects Overview:
-----------------

item_webSrv_{HostName}: Config Parameters for the Web server host.
   This config params include:
     - reference: pointer to the item_webDom
       for domain's information.  These
       domains are the one hosted by this hostname.
     - serverType: could be one of
       fullServer, ...

item_webDom_{domainName}: Information about a domain.
     - domainName
     - serverReference
     - doc basedir location

mmaWeb Object Processors and Containers:
----------------------------------------

    mmaWebServers.sh
```

```
    mmaWebDomains.sh

    mmaWebAdmin.sh

    bynameNspWebServers.sh
```

15.2.2 Files Overview – MMA Web

Extracted by mmaWebRoadmap.sh -i help

```
NAME
     mmaWebRoadmap.sh

SYNOPSIS
     Derived from seedActions.sh, use the -u.
     mmaWebRoadmap.sh -u

DESCRIPTION
     mmaWeb is a set of consistent policies built on
     (OSMT) Open Services Management Tools.

     mmaWeb Commands, each contain a set of related functions
     which allow you to accomplish specific tasks. Specifically:

     COMMAND                   TYPE               USED BY

     mmaWebLib.sh              library            any
     mmaWebServers.sh          subjectAction.sh   root/any
     mmaWebDomains.sh          subjectAction.sh   root/any
     mmaWebAdmin.sh            action.sh          root/any
     bynameNspWebServers.sh    action.sh          root/any

At A Glance
-----------

Basic web
-----------
  mmaWebLib.sh             --  To be used by mmaWebXXX family

  mmaWebServers.sh         --  Configure a system for web server.
       - For subject host, create apache
         conf file and update dns stuff

  mmaWebDomains.sh         --  Configure web domain
       - For subject domain, append the
         virtual domain info to apache
 conf file and update dns stuff.

  mmaWebAdmin.sh           --  Web server and domains maintenance.
```

```
ByName Support
--------------

  bynameNspWebServers.sh   --  Generate Web feature for byname subscriber.


USAGE
     See specific mmaWebXxxx  commands.

FILES
      mmaWeb*
```

15.2.3 Hints – MMA Web

IMAP

Extracted by mmaWebRoadmap.sh -i howTos

```
    A) How do I install new web server on my system?
       Follow the steps below.

       1) Make sure that the system has its input
          item in the mmaWebServerItems.site:
  item_webSrv_{hostName}

  domainRefList is a list of domains to be
  hosted by the system and it correspond
  to each item in mmaWebDomainItems.site itemsFile.

       2) ....
```

IMAP

15.2.4 Pointer and References – MMA Web

Extracted by mmaWebRoadmap.sh -i pointersAndReferences

```
Apache: http://www.apache.org
```

Part XIII

Database and Directory Facilities

Chapter 16

Name Services

16.1 nedaIPaddr.sh

16.2 opNetNameServices

Chapter 17

Directory Services Tools

Directory services is a set of tool that provides.....

17.1 Model and Terminology – Directory Services Tools

17.2 Files Overview – Directory Services Tools

17.3 Hints – Directory Services Tools

17.4 Pointer and References – Directory Services Tools

Chapter 18

Data Base Facilities

pgsql and mysql go here.

Part XIV

Security Facilties

Chapter 19

Key Management – Remote Access

lcaPgp Comes Here.

Chapter 20

Security Tools

20.1 opSecurity

opSecurity can be used as ....

Part XV

Development and Analysis Tools

Chapter 21

Development Facilities

21.1 CVS

Chapter 22

Software Management Tools

22.1 opSwPkgs

Chapter 23

Performance and Monitoring Tools

lcaNagios goes here.

Part XVI

Libre Content Production and Publication

Chapter 24

LaTeX

Chapter 25

Libre Content Processing

25.1 MMA Published Content

25.1.1 Model and Terminology – MMA Published Content

Extracted by mmaCntntRoadmap.sh -i modelAndTerminology

```
   Terminology and Model:
   ======================

pkgCombContainer      - the items file container of the
combined pkgs.

pkgFamily             - the family name that the pkg belong to.


Objects Overview:
-----------------

mmaCntntPkgItems.{pkgFamily}    - Items file for each family.
  Each pkg belongs to a family.
  Families are kept in separate items files.

item_cntntPkg_{pkgName}         - Information for each package.
  Each pkg reference points to
  item_access_{pkgName} which reside within
  the same file.

item_access_{pkgName}           - Complete access info for a pkg.
  Content type could be one of:
    sw,doc,svc.
  Each cntnt is restricted to one of:
    free,dist(distribution),conf(confidential)
```

```
mmaCntntPkgCombItems.{category} - Each combined package belongs to a
  category.  The category is one of:
  proj,usage,platform.  The category may
  increase over time.

item_cntntPkgComb_{pkgCombName} - Contain info for combined pkg.
  This include pointer to mmaCntntPkgItems.{pkgFamily}
  and pkg ref.

item_cntntPubSrvr_{hostName}    - Each host will published certain
  pkgs (combined or individual) according to
  this item.

A pkg can be one of these type:

    - "sw"
    - "svc"
    - "doc"

These then map onto http and ftp dirs based on the following
hierarchy.

    - ftp/http Roots

        - doc.dist  (For Distribution)
        - doc.conf  (Confidential)
        - doc.free  (Unrestricted)

- sw.free

- svc.free

    - origin (e.g. neda)

- family (e.g. leap)

    - pkgName (esro)

        - moduleName (mulPub)

    - revision

                                - accessPage (Generated)

       - categories

          - projs

          - owners

  - usage
```

```
               - accessPagesList
                 (Any Combination Pointing to accessPage)

mmaCntnt Object Processors and Containers:
------------------------------------------

    mmaCntntPkgs.sh
    mmaCntntPkgCombs.sh
    mmaCntntPubServers.sh
```

25.1.2 Files Overview – MMA Published Content

Extracted by mmaCntntRoadmap.sh -i help

```
At A Glance
-----------

Basic cntnt
-----------

  mmaCntntRoadmap.sh         -- This File. General Orientation and Information

  mmaCntntLib.sh             -- To be included in all mmaPubCntnt scripts.
                                General configuration parameters and
                                general useful functions go here

  mmaCntntPkgs.sh            -- Prepare each pkg for web and ftp transfer.
This includes copying source or docs
to the correct directory as well as
creating access page in html format
for each package.

  mmaCntntPubServers.sh      -- Prepare each host to become the
published content server.
```

25.1.3 Hints – MMA Published Content

Extracted by mmaCntntRoadmap.sh -i howTos

```
    A) How Do I setup a public content server from scratch?
```

25.1.4 Pointer and References – MMA Published Content

Extracted by mmaCntntRoadmap.sh -i pointersAndReferences

```
NOTYET
```

25.2 lcnLcnt

Chapter 26

Image Processing

Sections related to sane go here.

Chapter 27

Video Processing

publication. camcorder.

Chapter 28

Account Management Tools

28.1 Model and Terminology – Account Management Tools

Extracted by opAcctRoadmap.sh -i modelAndTerminology

```
   Terminology and Model:
   ======================



ITEM FILES
----------
```

28.2 Files Overview – Account Management Tools

Extracted by opAcctRoadmap.sh -i help

28.3 Hints – Account Management Tools

Extracted by opAcctRoadmap.sh -i howTos

28.4 Pointer and References – Account Management Tools

Extracted by opAcctRoadmap.sh -i pointersAndReferences

```
Mma man pages.
```

Chapter 29

Cron and At Tools

29.1 Model and Terminology – Cron and At Tools

Extracted by opCronRoadmap.sh -i modelAndTerminology

```
   Terminology and Model:
   ======================

 - cronEntry:

 - cronTable:

Objects Overview:
-----------------
```

29.2 Files Overview – Cron and At Tools

opAcctRoadmap-help.tex

Extracted by opCronRoadmap.sh -i help

```
DESCRIPTION
     opCron (MailMeAnywhere CRON) is a set of consistent
     policies built on the CRON as a CAPABILITY and on
     (OSMT) Open Services Management Tools.

     opCron Commands, each contain a set of related functions
     which allow you to accomplish specific tasks. Specifically:

     COMMAND                   TYPE             USED BY
```

```
     opCron.sh               action.sh         any

     opCronLib.sh            library.sh        root/any

     opCronActions.sh         action.sh  root/any


At A Glance
-----------

Basic qmail
-----------

  opCron.sh              -- This File. General Orientation and Information

  opCronLib.sh           -- To be included in all opCron scripts.
                              General configuration parameters and
                              general useful functions go here

  opCronActions.sh      -- Prepare binary files for qmail/ezmlm
                           -- for relevant pltforms and versions
```

opAcctRoadmap-help.tex

29.3 Hints – Cron and At Tools

Extracted by opCronRoadmap.sh -i howTos

```
    A-1) How Do I install Qmail on my system?
       Follow the steps below.

       0) Setup Open Services Platform Environment.
          In /opt/public/osmt/bin/
          source opEnvSet.csh -- . opEnvSet.ksh

       1) Disable the existing sendmail functionality
          mmaSendmailActions.sh -i sendmailDefunct

       2) Install Qmail Binaries.
          opCronBinsInstall.sh -i qmailFullInstall


    A) How Do I setup a null client from scratch?
       Follow (A-1), and then:
```

```
      3) Specify basic null client paramters (smarthost, domain, ...)
        In ../siteControl/nedaPlus/opCronListItems.main
        add an entry for your host. Then:

        opCronHosts.sh -s tehran -a configure

      4) Verify and Monitor installation

        opCronAdmin.sh -i fullReport

      5) Sendout a test message.

        opCronUserConfig.sh -i mailTest

      6) Allow users to customize their desired parameters.

        opCronUserConfig.sh

   B: How do I create a new binary kit for a new rev of Linux/SunOs?

      opCronBinsPrep.sh -i opCronBuildAndInstall
      opCronBinsPrep.sh -i opCronBinKitMake

   C: How Do I Setup an Domain Mail Server?

   C: How Do I Setup a mailing list?
```

29.4 Pointer and References – Cron and At Tools

Extracted by opCronRoadmap.sh -i pointersAndReferences

```
Cron man pages.
```

Chapter 30

sudo

Part XVII

Common Components – Service and User Environment

Part XVIII

Service Libre Components

Chapter 31

Printers Management Tools

31.1 opPrHosts

31.2 nedaPrint

nedaPrint is used to ....

Chapter 32

Voice Over IP (VoIP)

lcaVoipRoadmap goes here.

Chapter 33

Assigned Names and Numbers

33.1 Password File Accounts

Category	UID Range	GID Range	Naming Convention	Home Directory	Shell
System Acct	0 - 99		see Section...	/acct/sys	ksh
Employee	100 - 4999		see Section...	/acct/employee	ksh
Contractor	5000 - 9999		see Section...	/acct/contractor	ksh
Alumni	10000 - 14999		see Section...	/acct/alumni	ksh
Associate	15000 - 15999		see Section...	/acct/associate	ksh
Reserved	16000 - 19999				
Subscriber	20000 - 34999		see Section...	/acct/subs	ksh
User	35000 - 49999		see Section...	/acct/user	ksh
Program Acct	50000 - 54999		see Section...		ksh

33.1.1 Employee Account

33.1.2 Contractor Account

33.1.3 Alumni Account

33.1.4 Associate Account

33.1.5 System Program Accounts

User Name (Alias)	User ID	Group Name	Group ID
alias	50001	nofiles	50001
qmaild	50002	nofiles	50001
qmaill	50003	nofiles	50001
qmailp	50004	nofiles	50001

33.1.6 System Program Groups

User Name (Alias)	User ID	Group Name	Group ID
qmailq	50005	qmail	50002
qmailr	50006	qmail	50002
qmails	50007	qmail	50002

33.1.7 Subscribers (Authenticated)

Subscriber Group ID is 50004

	User Name (Alias)	User ID	Group Name	Description
Qmail	sa-00001 – sa-00003	15001 - 15003	subscrbr	Reserved
	sa-00004	15004	subscrbr	Subscriber 1.lastName.firstName
	.....			
EZMLM				
EMSD				

33.1.8 QMail Virtual Domain

	User Name (Alias)	User ID	Group Name	Group ID	Description
Qmail	qvd-0001	11001	virqmdom	50003	QmailVirDom freeprotocols.org
	qvd-0002	11002	virqmdom	50003	QmailVirDom byname.net
	qvd-0003	11003	virqmdom	50003	QmailVirDom byname.com
	qvd-0004	11004	virqmdom	50003	QmailVirDom bynumber.net
	qvd-0005	11005	virqmdom	50003	QmailVirDom bynumber.com
	qvd-0006	11006	virqmdom	50003	QmailVirDom emsd.org
	qvd-0007	11007	virqmdom	50003	QmailVirDom esro.org
	qvd-0008	11008	virqmdom	50003	QmailVirDom leapforum.org

Chapter 34

System Management and Configuration

34.1 Introduction

Below is the general road map to use OSMT tools for creating system environment.

```
INITIAL SETUP
=============
   - Operating System   -+
        - Installation   |     opGenesis.sh
        - Patching       }---- opSolAdmin.sh
        - Reproduction   |     opLinuxAdmin.sh
        - ...           -+

   - Profile & Identity          -+
        - Name assignment   }--- opSysIdentities
        - ...              -+

   - Account Generation             -+
        - Genesis                    |
        - employee, contractor, ...  }--- opAcctUsers.sh
        - subscriber                 |
        - ...                       -+

   - Disk Configuration & Access    -+    opDiskDrives.sh
        - mount disk                 |--- opDiskSegments.sh
        - Backup and Replication     |
        - ...                       -+

GENERAL FEATURES
================

   - Mail Configuration    -+
        - Qmail             |    mmaQmail.*
        - IMAP              }--- mmaImap.*
```

```
        - LEAP              |
        - ...              -+

   - Printer Configuration  }--- opPrHosts.sh

   - Web Configuration      }--- opWebServers.sh

   - Software               }--- opSwPkgs.sh

   - Name Servers
        - DNS
        - Hosts
        - ...

   - FTP Servers

   - Directory Services

   - Security

BYNAME FEATURES
===============

   - Mail Account    -+
                      |
   - LEAP             |
                      }-- bynameNsp*
   - Web Page         |
                      |
   - Subscriber      -+
```

34.2 opSysMgmtActions

This tool is used to ....

34.3 nedaSysMgmtActions

This tools is used specificcally for nedaPlus cluster...

34.4 dotIntra Cluster

Part XIX

User Environment Components

Chapter 35

ByStar Libre Emacs Office Environment (BLEOE)

Chapter 36

Wlan Facilities

Chapter 37

Browser Facilities

Part XX

Native Libre Components

Chapter 38

VoRDE

38.1 MMA VoRDE

38.1.1 Model and Terminology – MMA VoRDE

Extracted by mmaVordeRoadmap.sh -i modelAndTerminology

```
Terminology and Model:
======================
```

38.1.2 Files Overview – MMA VoRDE

Extracted by mmaVordeRoadmap.sh -i help

38.1.3 Hints – MMA VoRDE

Extracted by mmaVordeRoadmap.sh -i howTos

```
C: How Do I Setup a mailing list?
```

38.1.4 Pointer and References – MMA VoRDE

Extracted by mmaVordeRoadmap.sh -i pointersAndReferences

Mma man pages.

Chapter 39

LEAP

39.1 MMA EMSD

39.1.1 Model and Terminology – MMA EMSD

Extracted by mmaEmsdRoadmap.sh -i modelAndTerminology

```
Terminology and Model:
======================
```

39.1.2 Files Overview – MMA EMSD

Extracted by mmaEmsdRoadmap.sh -i help

39.1.3 Hints – MMA EMSD

Extracted by mmaEmsdRoadmap.sh -i howTos

```
C: How Do I Setup a mailing list?
```

39.1.4 Pointer and References – MMA EMSD

Extracted by mmaEmsdRoadmap.sh -i pointersAndReferences

```
Mma man pages.
```

Part XXI

Obsoleted or Deprecated Components

39.2 MMA Jetspeed

39.2.1 Model and Terminology – MMA Jetspeed

Extracted by bynameJetspeedRoadmap.sh -i modelAndTerminology

```
Part 3 of FIAS document also includes
relevant documentation.

New Documentation should be added here.

   Terminology and Model:
   ======================


Objects Overview:
-----------------


Templates:
----------

See Part 3 of FIAS.


State Table:
------------

See part 3 of FIAS.
```

39.2.2 Files Overview – MMA Jetspeed

Extracted by bynameJetspeedRoadmap.sh -i help

```
At A Glance
===========

  bynameJetspeedRoadmap.sh    -- This File. General Orientation and Information

  bynameJetspeedLib.sh        -- To be included in all bynameJetspeed scripts.
                                 General configuration parameters and
                                 general useful functions go here

  bynameJetspeedBinsPrep.sh   -- Prepare binary files for qmail/ezmlm
                              -- for relevant pltforms and versions
```

```
  bynameJetspeedServers.sh    -- For subject host, configure qmail

  bynameJetspeedAdmin.sh      -- Start, stop, Review Logs


Interfaces To Byname Module
===========================

  bynameJetspeedActions.sh    -- Called from Java code


Sychronization scripts? Where are they?
```

39.2.3 Hints – MMA Jetspeed

Extracted by bynameJetspeedRoadmap.sh -i howTos

```
 -) How Do I rebuild the *whole* byname system from sources?

    There are three steps invoved.

      1) Obtaining The Sources
         See: How Do I obtain the sources?

      2) Building The Package
         See: How Do I Build the ByName Package?

      3) Installing the Component And Activating The Server
         See: How Do I install the ByName component?
         See: How Do I administer the ByName component?

 -) How Do I obtain the sources?

    The build procedure expects that you are working in
       /sandbox/mine/pinneke
    You should also have access to the global CVSROOT.

     cd  /sandbox/mine/pinneke; /usr/devenv/mapFiles/byname/web/jetspeed/current.sh

     If you are doing development on the production side,

     cd  /l1/sandbox/mine/pinneke; /usr/devenv/mapFiles/byname/web/jetspeed/current.sh

  -) How Do I Build the ByName Package?

     From the Intra environment, obtain, all the byname needed content.
```

```
     cd  /sandbox/mine/pinneke; bynameJetspeedBinsPrep.sh -v -n showRun -s relCandidate -a zzzz

     Make sure that you are on the right machine/side where you
     want the package to be built. Then,

      bynameJetspeedBinsPrep.sh -v -n showRun -s relCandidate -a srcBuildAndPkg

   -) How Do I install the ByName component?

      bynameJetspeedServers.sh -v -n showRun  -s tehran -a compUpdate

   -) How Do I administer the ByName component?

      bynameJetspeedAdmin.sh

 -) Once a full build is in place how do I do quick cycle development?

    o- bynameJetspeedBinsPrep.sh -v -n showRun -s relCandidate -a srcBuild

    o- bynameJetspeedServers.sh -v -n showRun  -s tehran -a jetspeedUpdate

    o- bynameJetspeedServers.sh -v -n showRun  -s tehran -a serviceRestart

 -) How to customize between byname.com and byname.net
    content?

    In order to be able to customize the content of
    the web page, velocity is used to embed dynamic content
    in web sites.  User guide is available at:
    http://jakarta.apache.org/velocity/user-guide.html.

    You need to create a file named bynameConfigFile.vm.bynametmpl
    in /sandbox/mine/pinneke/byname-jetspeed/webapp/WEB-INF/templates/vm
    This config file will have the following variable:

         #set(  = "<!var:domainName>" )

    This file will be included inside the content that
    need to be customize for the .com or .net

    For example: the logo for byname.com and byname.net
    has to be different depending on the domain.
    The file that are responsible for this action is in
    /sandbox/mine/pinneke/byname-jetspeed/webapp/WEB-INF/templates/vm/layouts/html/default.vm

    Inside this file, put the following:

    #parse( "bynameConfigFile.vm" )
    .....
    .....
```

```
    ..... (any HTML tag)
    #if ( "" == "byname.com.intra" || "" == "byname.com" )
     <TD><IMG SRC=".setURI("byname/images/comlogo.gif").Absolute" /></TD>
    #elseif ( "" == "byname.net.intra" || "" == "byname.net" )
     <TD><IMG SRC=".setURI("byname/images/netlogo.gif").Absolute" /></TD>
    #end

   After you edit this file, do quick cycle.
   (See: Once a full build is in place how do I do quick cycle development?)

   The bynameJetspeedBinsPrep.sh will call the bynameJetspeedServers.sh to
   update jetspeed.  When bynameJetspeedServers.sh is called, it looks for all
   the files that end with .bynametmpl and doing global replacement
   for <!var:xxxx> with wahtever specified in the bynameJetspeedServers.sh.
```

39.2.4 Pointer and References – MMA Jetspeed

Extracted by bynameJetspeedRoadmap.sh -i pointersAndReferences

http://jakarta.apache.org/